




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>G11B 20/00, H04N 5/913, 7/16, G11B 27/10, 27/28, 27/34, 19/02, 20/12, H04N 5/926, 9/804, 5/937, 9/877, 5/85 // G11B 7/00</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 97/06531</b></p> <p>(43) International Publication Date: <b>20 February 1997 (20.02.97)</b></p>									
<p>(21) International Application Number: <b>PCT/JP96/02188</b></p> <p>(22) International Filing Date: <b>2 August 1996 (02.08.96)</b></p> <p>(30) Priority Data:</p> <table border="0"> <tr> <td>7/200122</td> <td>4 August 1995 (04.08.95)</td> <td>JP</td> </tr> <tr> <td>7/200121</td> <td>4 August 1995 (04.08.95)</td> <td>JP</td> </tr> <tr> <td>95202215.0</td> <td>16 August 1995 (16.08.95)</td> <td>EP</td> </tr> </table> <p>(34) Countries for which the regional or international application was filed: <b>NL et al.</b></p> <p>(71) Applicants (for all designated States except US): <b>SONY CORPORATION [JP/JP]; 7-35, Kitashinagawa 6-chome, Shinagawa-ku, Tokyo 141 (JP). PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).</b></p> <p>(72) Inventors; and</p> <p>(75) Inventors/Applicants (for US only): <b>KAWAMURA, Makoto [JP/JP]; Sony Corporation, 7-35, Kitashinagawa 6-chome, Shinagawa-ku, Tokyo 141 (JP). FUJINAMI, Yasushi [JP/JP]; Sony Corporation, 7-35, Kitashinagawa 6-chome, Shinagawa-ku, Tokyo 141 (JP). DE HAAN, Wiebe [NL/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).</b></p>		7/200122	4 August 1995 (04.08.95)	JP	7/200121	4 August 1995 (04.08.95)	JP	95202215.0	16 August 1995 (16.08.95)	EP	<p>(74) Agents: <b>KOIKE, Akira et al.; 11 Mori Building, 6-4, Toranomon 2-chome, Minato-ku, Tokyo 105 (JP).</b></p> <p>(81) Designated States: <b>AU, BR, CA, CN, CZ, KR, MX, RU, SG, US, VN, European patent (AT, DE, ES, FR, GB, IT).</b></p> <p><b>Published</b></p> <p><i>With international search report.</i></p> <p><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
7/200122	4 August 1995 (04.08.95)	JP									
7/200121	4 August 1995 (04.08.95)	JP									
95202215.0	16 August 1995 (16.08.95)	EP									

(54) Title: **INFORMATION CARRIER, DEVICE FOR READING AND DEVICE FOR PROVIDING THE INFORMATION CARRIER AND METHOD OF TRANSMITTING PICTURE INFORMATION**

## (57) Abstract

The disclosed system comprises an information carrier (1) on which an information signal is recorded that represents picture information intended for being displayed on a picture screen, which picture information comprises video information of a video program as well as control information for selectively displaying the video programme. The video programme is subdivided into sections (35) and, when the video programme is displayed selectively, sections are shown in a new order (34) and partly omitted or replaced. To this end the control information includes path information (36) which indicates a path of sections to be displayed in linked fashion. The path information may be recorded multiplexed with MPEG-2 video information and then contains addresses (53, 54, 55, 56, 57, 58, 59) for forward and backward jumps.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Larvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## DESCRIPTION

INFORMATION CARRIER, DEVICE FOR READING  
AND DEVICE FOR PROVIDING THE INFORMATION CARRIER  
AND METHOD OF TRANSMITTING PICTURE INFORMATION

## TECHNICAL FIELD

The invention relates to an information carrier on which an information signal is recorded, the signal representing picture information intended to be displayed on a picture screen, the picture information comprising video information of at least a single video program and control information for displaying various versions of the video program.

The invention further relates to a device for reading and a device for providing the information carrier.

The invention also relates to a method of transmitting picture information via the information carrier. Such an information carrier, reading device and transmitting method are disclosed in published U.S. Patent No. 4,930,158. On the known information carrier, such as, for example, a video tape, a video program is recorded and for fully reproducing the video program the information carrier can be read on a standard playback system. When played back on the known

system, the video program may also be reproduced selectively while certain parts of the video program are not displayed. For this purpose, the video signal repeatedly contains classification codes, for example, via digital codes stored on an invisible video line. The recovered classification code is compared with a classification selected by the user and, in dependence on the result, the replay is interrupted or the output signal is blocked until a permitted classification code is detected. This may avoid, for example, children viewing pornographic or violent scenes.

#### BACKGROUND ART

A problem with the known information carrier is that the picture reproduction is interrupted during selective replay when classified parts of the video signal occur. Such an interruption is continued until again a permitted classification code is detected in the video signal. These interruptions cause the viewing of the video program during selective replay to be annoying, the more so because one does not know how long such an interruption will last.

More specifically still, this invention relates to a method of recording time-division multiplexed compressed audio and video data on a data recording medium, a method of reproducing such data, an apparatus for recording such data,



and an apparatus for reproducing such data. A data recording medium may take a number of different forms, including magnetic tapes or disks, magneto-optical disks, optical disks, semiconductor memory, and the like.

In the production of video works, e.g. motion pictures, television programs, etc., it is commonplace for different versions of a particular work to be created. Although sharing certain video images and portions of soundtrack, each version of a work can differ from others by including or excluding other images and audio segments. For example, certain scenes of a motion picture may be cut entirely or a selection may be made from a number of different photographed versions of a particular scene. Such versions may be created to satisfy management concerns or to reflect political policy or cultural standards. Multiple versions of a work may be created, each work having a different length and each being adapted particularly for display in a theater, for transmission via television broadcast, or for recording/reproduction by domestic consumer recording/reproducing devices.

Further, the version of a work initially released to a market may be later modified and re-released to reflect changed circumstances or the author's intention. For example, a director may re-edit a work to produce a "director's cut edition" which differs from the originally-

released version. Further, a "complete edition," a "special edition," and so forth may also be produced in connection with a particular work.

Particularly relevant to the present invention is the international practice of rating video works according to the content of the work, e.g. certain material is determined to be unsuitable for viewing by certain audiences. In some countries, video works are designated for viewing by only adult audience while minor-aged persons are prohibited from viewing or purchasing such works. In the United States, the rating system is not law but is a voluntary system adopted by film makers, distributors, and sellers. According to this voluntary system, movies may be classified into the following five categories: G - General audiences, all ages permitted; PG - Parental Guidance Suggested, some material may not be suitable for children; PG-13 - Parents strongly cautioned, some material may be inappropriate for children under the age of 13; R - Restricted, children under the age of 17 must be accompanied by a parent or adult guardian; and NC-17 - No children under the age of 17 admitted. In accordance with this system access to certain video works, whether displayed in a theater or available for purchase or rental on a prerecorded video media, has been restricted for certain categories of consumers. Inherent in this system has been

the practice of rating an entire video work as a whole as opposed to rating component portions.

Compliance with the voluntary rating system in connection with video works available on prerecorded media may be increased by implementing a rating monitoring system in the device for reproducing the video work. The video work is coded with an indication of its rating, e.g. a flag indicating adult entertainment is written to the prerecorded media, and this coding is detected by the reproduction system. When it is determined that the viewer does not meet the rating criteria, reproduction of the video work is prohibited.

In a European digital telecasting system, a "Parental Rating" function is available. Where a scene of a program deserves a particular rating, a rating identification code is placed before the beginning of the program. In "rating" mode, the receiver is able to receive/display only those programs consistent with the parental rating. Specifically, the receiver detects the rating identification code at the start of the video program and discontinues reproduction of the program if its rating is inconsistent with the parental rating. In this manner, viewing of a program can be inhibited.

As an alternative to the above-described system, viewer compliance with video program rating may be achieved on a

scene-by-scene basis. A rating code may be inserted before a particular scene for detection by the reproduction system. If the rating code is inconsistent with a previously established rating, the rated scene may not be reproduced and "noise" or another video image or scene may be displayed. Normal reproduction of the original video program is resumed once the rated scene comes to a close.

Such a system has the disadvantage that the continuity of the display of the program is interrupted. If the length of the rated scene is not known to the viewer, the "noise" or other temporary image is necessarily viewed until display of the original program is resumed. Similarly, when the program is reproduced from a prerecorded medium, a special reproduction operation, such as high-speed search, may be initiated by the reproduction device upon detection of the rating identification code. In certain implementations, such a system may suffer the disadvantage of reproducing for viewing the rated scene.

Japanese patent application Hei-6-335602 describes two techniques for reproducing a video work from a prerecorded medium. In one reproduction operation, only unrestricted portions of a video work are reproduced. In another reproduction operation, restricted portions of a video work are reproduced. The reference does not describe the utilization of rating identification codes in connection with

scenes of a video work.

### DISCLOSURE OF INVENTION

It is an object of the invention, for example, to provide means for transmitting video information by which a video program can be reproduced selectively substantially without interruptions.

According to a first aspect of the invention, an information carrier of a type defined in the opening paragraph is characterized in that the control information comprises path information indicative of one or more versions of video information sections to be reproduced in a linked fashion, the path information being indicative of sections to be reproduced consecutively. The information carrier according to the invention is advantageous, for example, in that the path information indicates a path of linked sections, so that a next section can be sought rapidly once the end of a section has been reached. As a result, a substantially continuous reproduction of a selective version of the video program is possible. In addition, the sections may be selected differently for each version; so that various versions are formed from the same video program.

It is a further object of the invention to provide means for transmitting picture information, so that a basic

version of the video program can be reproduced on a device not arranged for selective playback. An embodiment of the information carrier according to the invention is therefore characterized in that the video information of a video program is subdivided into two portions, the first portion comprising the video information of a basic version and the second portion comprising additional video information, and a version comprising at least one section of the additional video information. The additional video information does not form part of the non-selective basic version of the video program. The inclusion of a section of the additional video information in a version creates a selective version of the video program, whereas the basic version can also be played back on a player that is not arranged for reproducing sections that are interlinked along a path. This is furthermore advantageous in that, for example, a more aggressive scene may be substituted for another scene without disturbing the story of the video program. Alternatively, a longer version of the video program may be formed, such as, for example, a director's cut.

A further embodiment of the information carrier according to the invention is characterized in that the sections are addressable and in that the path information comprises addresses of sections to be displayed consecutively. This is advantageous in that a playback

device can search for the destination in the fastest possible way after a section has ended, for example, the read head of a playback device for an optical disc can jump forthwith to the address of the next section.

A further embodiment of the information carrier according to the invention is characterized in that the path information comprises playtime information. This is advantageous in that the user can be shown the exact playtime of a version after the selection. During selective playback, this exact playtime will differ from the original playtime.

A further embodiment of the information carrier according to the invention is characterized in that the path information comprises track information indicative of a subdivision into tracks, while the tracks are numbered independently for each video program. This is advantageous in that the user has the disposal of a logical track arrangement with tracks numbered from 1 upwards for each video program. In addition, a numbering in sequential form can be used for each version.

A further embodiment of the information carrier according to the invention is characterized in that path information for displaying each version is recorded in an information carrier area that can be located. This is advantageous in that the path information of any desired version can be recovered in a simple manner.

A further embodiment of the information carrier according to the invention is characterized in that the path information is recorded on the information carrier near to entry points, while playback is possible from the entry points without the use of previous picture information. This is advantageous in that relevant path information is available forthwith when a jump is made to an entry point in the video program and when the picture display is started from an entry point.

A further embodiment of the information carrier according to the invention is characterized in that the information carrier is subdivided into addressable sectors and in that the path information near to an entry point comprises address information relative to the respective entry point. This is advantageous in that, when a jump is made, the jump distance for controlling the reading system is known from an entry point.

A further embodiment of the information carrier according to the invention is characterized in that the video program is subdivided into tracks and in that the path information near to an entry point comprises address information indicative of the beginning of the next track in the respective version. This is advantageous in that a next track can forthwith be jumped to during playback.



A further embodiment of the information carrier according to the invention is characterized in that the path information near to an entry point comprises address information of video information to be displayed beforehand. This is advantageous in that during reverse playback a previous section or track can simply be found back.

A further embodiment of the information carrier according to the invention is characterized in that the path information near to an entry point comprises time code information indicative of the playtime from the beginning of the respective version. This is advantageous in that a continuously running time indication is available from the start of a specific version that is played back.

According to a second aspect of the invention, a device for reading an information carrier of a type defined in the opening paragraph, the device comprising first means for recovering the picture information and control means for selectively reproducing the video program in response to the control information, is characterized in that the control information comprises path information indicative of one or more versions of video information sections to be reproduced in linked fashion, the path information being indicative of sections to be reproduced consecutively, and in that the device comprises second means for recovering the path information and in that the control means are adapted for

consecutively reproducing the video program sections in response to the path information. This is advantageous, for example, in that selective versions of a video program, built up from consecutive sections in an order denoted by the path information, are displayed substantially or completely without interruptions.

An embodiment of the device according to the invention is characterized in that the path information comprises playtime information and the device comprises means for displaying the playtime in response to the path information. This is advantageous in that a user is shown the real playtime of the selected version.

A further embodiment of the device according to the invention is characterized in that path information for displaying each version is recorded in a locatable area of the information carrier and in that the second means are adapted for locating the area. This is advantageous in that any possible version is known and can be stored in a memory after the area has been located and the path information has been recovered. As a result, the device can timely read the video information necessary for a specific version. It is also possible to skip directly to a specific part of a version.

A further embodiment of the device is characterized in that path information is recorded on the information carrier

near to entry points, while playback is possible from the entry points without the use of previous picture information, and in that the second means are adapted for recovering the path information near to entry points. This is advantageous in that, after a jump to another item of the video program, the path information relative to that item is available forthwith. Consequently, a large memory in the playing device for retaining all the path information has become redundant.

A further embodiment of the device is characterized in that the path information near to an entry point comprises address information of video information to be displayed beforehand, and in that the control means are adapted for displaying the picture information in reverse direction in response to said addresses. This is advantageous in that a selective version of the video program can also be displayed in reverse direction substantially without interruptions.

A further embodiment of the device is characterized in that the path information near to an entry point comprises time code information indicative of the playtime from the beginning of the respective path, and in that the device comprises means for displaying the playtime in response to the time code information. This is advantageous in that the user can be shown a continuously running time indication from the beginning of the playing of the version.

According to a third aspect of the invention, a device for providing an information carrier of a type defined in the opening paragraph, the device comprising means for coding the picture information and means for recording the information signal on the information carrier, is characterized in that the control information comprises path information indicative of one or more versions of video information sections to be shown in linked fashion, the path information being indicative of sections to be displayed consecutively, and in that the device comprises means for generating the path information and means for adding the path information to the picture information.

According to a fourth aspect of the invention, a method of transmitting picture information intended for being displayed on a picture screen via an information carrier on which an information signal representing picture information is recorded, this picture information comprising video information of at least one video program and control information for displaying various versions of the video program, is characterized in that the control information comprises path information indicative of one or more versions of video information sections to be shown in a linked fashion, the path information being indicative of sections to be displayed consecutively. This is advantageous in that a plurality of versions of a video program can be transmitted

via information transfer while the necessary transmission and storage capacity remains restricted.

A still further object of the present invention is to provide apparatus for recording on an information carrier different versions of a video work, each version including one or more portions of the work.

Yet another object of the present invention is to provide apparatus that allows a user to select among plural recorded versions of a work a version for reproduction that is consistent with the user's preferences.

Another object of the present invention is to provide apparatus for reproducing different versions of a work according the rating assigned to the work.

According to a fifth aspect of the present invention, a method for displaying one of a plurality of versions of a program recorded on an information carrier is provided. The method includes the steps of: displaying to a user rating information regarding at least two of the versions of the program; receiving from the user a selection of one of the versions; reproducing from the information carrier the selected version for display to the user.

According to a sixth aspect of the present invention, a method for recording a plurality of versions of a program on an information carrier, where each version may include a number of program sections, is provided. The method includes

the steps of: encoding the program sections to produce encoded program sections; appending an address information to each of the encoded program sections; appending a version information to each of the encoded program sections; and recording the encoded program sections, including the address information and the version information, on the information carrier.

According to a seventh aspect of the invention, a method for reproducing one of a plurality of versions of a program recorded on an information carrier, where the versions include a plurality of program sections, is provided. The method includes the steps of: reproducing from the information carrier a first program section that includes a plurality of version information and a plurality of address information; detecting in the first program section a version information corresponding to the one version and an address information corresponding to the version information; and reproducing from the information carrier a second program section according to the address information.

According to an eighth aspect of the invention, a method for reproducing one of a plurality of versions of a program recorded on an information carrier, where the versions include a plurality of program sections, is provided. The method includes the steps of: reproducing from the information carrier a version information corresponding

to the one version and an address information corresponding to the version information; and reproducing from the information carrier a program section according to the address information.

Apparatuses corresponding to each of the fifth, sixth and seventh aspects of the invention are also an aspect of the present invention.

These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter. Other objects, features and advantages according to the present invention will become apparent from the following detailed description of illustrated embodiments when read in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF DRAWINGS

In the drawings:

Fig. 1 shows a system for picture information transmission,

Fig. 2 shows an information carrier,

Fig. 3 shows a video program and several paths of sections,

Fig. 4 shows a video program and additional video information as well as a path,

Fig. 5 shows a part of a video program with path information near to entry points,

Fig. 6 shows a path\_descriptor,

Fig. 6A shows a path\_descriptor syntax,

Fig. 6B shows a path\_descriptor,

Fig. 6C shows a time\_code\_descriptor(),

Fig. 7 shows a TOC structure,

Fig. 8 shows a device for reading an information carrier,

Fig. 9 shows a device for providing information carriers

Fig. 10 shows a data format for recording information on an information carrier,

Fig. 11 shows a data format according to ISO 9660,

Fig. 12 shows a disc table of contents,

Fig. 12A shows a disc\_tracks area,

Fig. 13 shows a program table of contents,

Fig. 13A shows a program\_tracks,

Fig. 13B shows a path\_table,

Fig. 14 shows the formation of different versions of a program,

Fig. 15A shows a program stream,

Fig. 15B shows a PES packet,

Figs. 16A, 16B, 16C and 16D show a PES packet,

Fig. 17 shows a multiplexed bitstream,



Fig. 18 shows a multiplexed bitstream that includes entry points,

Fig. 19 shows a data recording device,

Fig. 20 shows a multiplexing unit,

Fig. 21 shows a data reproducing device,

Figs. 22A and 22B show a PSM packet,

Fig. 23A shows a completed access unit,

Fig. 23B shows an uncompleted access unit,

Figs. 24A and 24B show different arrangements of video data,

Fig. 25 shows a bitstream including plural data sequences,

Figs. 26A, 26B and 26C show a reproduction operation, and

Figs. 27A, 27B and 27C show entry points in plural sections.

#### BEST MODE FOR CARRYING OUT THE INVENTION

Elements in the drawing Figures corresponding to elements already described carry like reference characters.

Fig. 1 shows a system for picture information transmission via an information carrier 1. The picture information is transmitted via an information signal. Picture information contains not only video information, but

also any information related to the picture such as, for example, sound, subtitles and control information. An amount of video information that is intended to be displayed as a whole is called a video program. The device 2 for providing the information carrier codes picture information supplied thereto through input 4 and modulates the information signal with the coded picture signal and subsequently records the modulated information signal on the record carrier 1. The reading device 3 reads the information carrier 1 and demodulates and decodes the information signal and reproduces the picture information for the user on output 5. For example, a magnetic tape or an optical disc such as a laser disc or digital video disc may be used as an information carrier. The information signal may also be transmitted to a user via a network from an information carrier in a central storage means, such as a video server, in which case the user's commands are transferred to the video server. The information signal is at least a representation of the video information, such as, for example, an analog video signal according to the PAL or NTSC standard, or a digitally coded and compressed video signal according to MPEG-1 or MPEG-2. The information signal is furthermore a representation of the control information coded by information symbols. In the case of an analog video signal the symbols may be co-transmitted in the format of digital signals during

horizontal or vertical blanking, such as, for example, in the known Teletext system. In the case of a fully digital picture signal, such as MPEG-2, a separate data stream of user data may be co-transmitted by multiplexing, for example, by subdividing the digital stream into packets of, for example, 2048 bytes and providing these packets with a header that denotes the type of information. With respect to MPEG-2, the coding of picture information is described in the international ITU/ISO 13818-2 standard, and the ITU/ISO 13818-1 standard (proposed in ISO/IEC JTC1/SC29/WG11, November 13, 1994) describes how elementary streams of coded video data are multiplexed with other coded data which are representative of, for example, audio and subtitles to become a program stream. Information of a type not specified by MPEG-2 may be included in "private packets" in an arbitrary format. MPEG-2 packets with an additional header of the prescribed format are then distinguished as "private stream 1", and without as "private stream 2".

Fig. 2 shows a disc-shaped optically readable information carrier 1, such as a CD or laser disc. The information signal representing picture information intended for being displayed on a picture screen is recorded in a helical or concentric track 21. The picture information and the information signal are described with reference to Fig. 1. A description of recording and reading a CD may be found,

in the title 'Principles of optical disc systems' by Bouwhuis et al., ISBN 0-85274-785-3. The track is subdivided into addressable sectors 22. The information carrier may contain a Table Of Contents 24 (TOC) in which a reference to the information of one or more video programs is included. The TOC 24 is located at a fixed position on the information carrier. The information carrier may also have an information structure in which the space available for information storage is arranged in directory Tables for the storage of specific information. An example of this is described in ISO 9660 standard, in which information storage in files 23 is effected via directory Tables. These directory Tables may be located via a reference address at a fixed position at the beginning of the area intended for the information storage.

Fig. 3 shows a video program and several section paths according to the invention. A video program is shown diagrammatically by a bar 30. The video program can be played in the original, non-selective version from beginning to end without interruptions along a basic path 31. For selective playback, the video program is subdivided into sections 35 for each version. The original version is shown by the basic path 31, the total video program being considered a single section A. When playback is effected along the basic path 31, the video information is shown in

the order it was recorded. Playing a selected version along a path 32 is shown diagrammatically by line sections 35 to be displayed and jumps with interrupted line sections 36.

For a first version, the total video program is subdivided into sections B, C and E, section B being the beginning, C being a short middle section and section E being the end. The path information denotes the linking information from B to C and from C to E as is indicated by the interrupted line sections 36. Once a section B has been played back, the reading of the information carrier is continued at the beginning of the next section C, while the intermediate area is covered by a jump. In consequence, a first version of the video program B-C-E arises in which certain parts of the original are skipped. For a second version which has a longer middle section, section D is given, which contains section C surrounded by video material. The second version then consists of the sections B, D and E for which less video material is skipped than for the first version. The path information for the second path comprises the beginnings and ends of the sections B, D and E and the linking information from B to D and from D to E, as well as the information that E is the last section. Thus, in this manner the path information provides after section B an option to split, which option depends on the version selected.

In another embodiment of the information carrier 1, each path is indicated from beginning to end of the respective version of the video program, such as indicated, for example, by another version 33 for which the video program is subdivided into the sections F, G, H and I. The route along the particular path is indicated as F, H, G and I by the linking information, so that section H is thus shown prior to a section G, whereas in the recording order H comes after G. However, the linking information may provide an entirely random path for which the recording order does not pose any restrictions. There may also be observed that the last section I, and thus the playback part, ends earlier than the original video program. For that matter, the path information indicates forthwith that no further video information need be reproduced any more. Alternatively, it is possible to record a type indication for each section, for example, start section, middle section or end section.

Fig. 4 shows a video program subdivided into two parts, that is, basic video information 30 and additional video information 40. Thus, additional video information 40 is recorded in addition to the original video program 30. The original version is indicated by the basic path 31 and section A. This basic version can also be played back on a simple device that lacks the means for recovering the path information. Sections K and L are indicated in the original

video program, and the sections X and Y are indicated in the additional video information 40. A selective version of the video program is indicated by part 41, formed by the sequence of sections K, X, L and Y. Such a path thus includes at least one section of the additional video information. This develops an alternative version of the video program, for example, a happy ending, or an extended version according to the director's personal taste, a "director's cut." It is also possible to assemble modified versions for specific countries, religions, habits or political ideologies.

The linking information makes a direct jump possible when the end of a section is displayed, so that a substantially continuous picture display is obtained. When a tape is used as an information carrier, the beginning of the next section may be reached with only a brief interruption of the video program by "fast forward". In the case of a disc a brief jump in radial direction to the initial address of the next section is possible. A continuous display is realized if shortly before a jump a buffer is loaded with video information displayed during the jump. For that matter, the position of the next section to be displayed is known.

A suitable embodiment of the linking information is a Table in which any possible subsequent sections are stored for each section, as is indicated at 32 in the first example.

At section B there is indicated that sections C and D can be linked. Selection parameters such as a classification code may be assigned to each section and stored in the Table in addition to the initial and final addresses. A selection of a next section from the available linkable sections may then be derived from the selection parameters. Another embodiment of the linking information is a Table for each path with consecutive sections, in which sector addresses of the first and last sectors of each section are stored. Also the total number of sections, i.e. the length of the Table, is stored, so that the end of the respective version is known. For each video program the number of paths is recorded or a Table is included for a given fixed number of paths. In the latter case the Tables have a number of sections equal to 0 for unused paths. In another embodiment, the video information is segmented while a section is formed by one or more successive sections. A Table for a path then contains addresses of all segments which in the given order form a specific version. The segments may thus be recorded consecutively, so that it is not necessary to jump after each segment. In such a Table a section boundary thus appears from a jump.

The path information always contains at least linking information for consecutively displaying sections of video information. This linking information may directly indicate



the addresses 22 of the respective sectors of the information carrier, but in another embodiment indicators for the sections are smaller segments, so that the video signal may be included consecutively in its stead. In that case, a separate Table of indicators and addresses of sections or segments is recorded. This Table then contains, for example, always a segment number and the initial and final addresses of the segment.

From that which precedes it appears that the playtime of the selective versions of the video program may have a playtime that differs from the original video program. For that matter, video material is skipped or added. In an embodiment of the information carrier, the playtime information is added to the path information. For example, the playtime is indicated for any possible path. It is also possible to include the playtime per segment or per section, while the total playtime can be calculated by adding up these playtimes for the respective version. This provides the possibility of reading the playtime of the version selected by the user from the information carrier and displaying same to the user.

In a disc-shaped information carrier as described with reference to Fig. 2, it is attractive to store path information in a file. Via the Directory Tables the information relating to a path may be located and read

rapidly. After the information carrier is inserted into a player, the path information is available forthwith. On other information carriers and playback equipment the path information may be recorded in an area that is easy to locate, such as, for example, at the beginning of a tape. In another embodiment of the information carrier, the path information is recorded next to the respective video information spread over the carrier, as is described with reference to Figs. 5 and 6. In consequence, the file need not constantly be located and read or, once read, be stored in a large memory in the player. After a jump, the respective path information can be read forthwith from the information carrier. Alternatively, it is possible to combine these embodiments in that the path information is recorded multiple times. A survey of path information is then available in a central file whereas, besides, path information multiplexed with the video information is recorded.

Fig. 5 shows a part of a video program, in which the path information is indicated near to a specific point in the information stream. In this path information may be used absolute addresses for the jump instruction, but also relative jump addresses with respect to said point. An advantage of the relative jump addresses is that the servo means in the player may take account of the distance to be

jumped. A path for a selective version is referenced 34. The video signal is coded digitally then, such as MPEG-2. For this coding, always a number of video frames are coded dependently by forward or backward computation (P-frame), or bidirectionally (B-frames) in the case of an independently coded frame (I-frame). Playback may then be started only from an I-frame and not from a dependent B or P-frame. The I-frame comprises an intra-coded picture, while the P-frame comprises a predictive encoding of a picture and the B-frame comprises a bidirectional predictive encoding of a picture. An I-frame alone, or along with a number of B-frames and/or P-frames may be considered together as a group of pictures (GOP).

The video signal is subdivided into segments 52 which comprise each at least a single I-frame. The beginning of such segments 52 is designated by entry points 51. After an entry point 51, the video signal first contains an I-frame. This spacing of entry points 51 may vary; about two entry points per second of playtime is a usual number. In the case of a jump, always the sector address of an entry point 51 is taken as the destination address. In an embodiment of an information carrier according to the invention, also path information is recorded near to an entry point. Further description of entry points is available in Japanese patent application Hei-4-277956.

In Fig. 5 the path information is recorded as packets of control information in the segments 52 directly following entry points 51. The packets of the path information are marked as control information, for example, as Program Stream Map (PSM) packets in the manner customary for MPEG-2. Reference be further made to the ISO 13818-1 standard mentioned with reference to Fig. 1. ISO 13818-1 further defines a program stream directory (PSD) and a sector that includes both a PSM and a PSD is termed an entry sector.

An entry point may be defined by an entry packet provided directly ahead of the packet where the first I-frame of the GOP exists. The entry packet may be associated with an identification flag and position information regarding three neighboring entry points. Such position information may include the distance from the entry point to the neighboring entry point. Alternatively, an entry point may be defined simply by appending an identification code to a regular data packet.

By jumping from one entry point to a neighboring entry point, I-frames can be efficiently located to facilitate "high-speed search"-type reproduction operations.

The Program Stream Map according to the invention describes the contents of the information stream in descriptors. They are information structures describing the different information streams in the total multiplexed

information stream, such as the video, audio or subtitle stream, but also, for example, the paths. An actual time code, tracks and sections are given for each path. Time codes denote the period of time elapsed since the beginning of the programme or track. Tracks denote a subdivision for the user of a total program and track numbers are denoted T4, T5, T6 and T7 in Fig. 5. In a path it is also possible for a jump to occur within a track, as is denoted by the arrows 60 at T6.

Fig. 6 shows an example of a path\_descriptor of a path. A descriptor commences with a descriptor\_tag which denotes the type of descriptor and a descriptor\_length. The path\_number denotes for which path the data in the descriptor are intended. The time codes pX\_track\_tc and pX\_path\_tc from the beginning of the actual track and from the beginning of the actual path respectively, are valid at a specific system instant denoted by the Presentation Time Stamp PTS in a manner customary in MPEG-2. The system time is also contained in the video signal, so that a proper synchronization between the various types of information may be achieved. After a jump, however, there may be a discontinuity in the system time, so that this system time is unsuitable for denoting the elapsed playtime. A track\_number denotes the track number of the respective path.

A more complete definition of the `path_descriptor()` area is illustrated in Fig. 6A. The `path_descriptor()` area defines areas for various paths and describes the path number, track number, sector number, sector offset, track time codes and path time codes. Alternatively, areas for track number, track time codes, and path time codes may be defined in another area, such as a `time_code_descriptor` for common definition for all paths.

Preferably, the path number (`path_number`) is a 3-bit value providing a path number which identifies the descriptor. The track number (`track_number`) is preferably a 16-bit value representing the current track number encoded relative to the program start position. The track number of a segment may be used by one or more paths and may be incremented via the path. The absolute track number may be determined from the relative track number and the track number offset stored in `program_linkage` area of the `D_TOC` area.

The sector number (`pX_sectors_to_read`) is preferably an unsigned integer indicating the number of sectors, inclusive, remaining prior to the end of the program section for the particular path. If the sector number (`pX_sectors_to_read`) is zero, then that sector is not a portion of that particular path.

The sector number (`pX_sectors_from_start`) is preferably an unsigned integer indicating the number of sectors between the that sector in the particular path from the start position of the current section. If `px_sectors_from_start` has a zero value then that sector is the first sector of the section. Note, a program is comprised of one or more sections. Each section is comprised of one or more sectors.

The offset (`pX_offset_next_section`) preferably indicates the number of sectors in the particular path between the entry sector of the current section and the entry sector at the start position of the next section. If `pX_offset_next_section` equals zero, then the last section according to the particular path has been reached.

The offset (`pX_offset_previous_section`) preferably indicates the number of sectors in the particular path between the entry sector of the current section and the last entry sector in the immediately previous section. If `pX_offset_previous_section` equals zero, then the current section according to the particular path is the first section to be reproduced.

If `pX_sectors_to_read`, `pX_sectors_from_start`, `pX_offset_next_section`, and `pX_offset_previous_section` each equal zero then the particular path is not in use or the entry sector does not constitute a part of that particular path.

The offset (`pX_offset_next_track`) is preferably the sector offset from the current sector of the particular path to the entry sector of the start position of the next track. If `pX_offset_next_track` equals zero, then the current track is the last track of the particular path.

The offset (`pX_offset_start_track`) is preferably the sector offset from the current sector of the particular path to the entry sector of the start position of the current track. If `pX_offset_start_track` equals zero, then the current track is the first track of the particular path. If the current entry sector is the leading sector of the current track, then `pX_offset_start_track` represents the offset to the start position of the previous track.

The track time codes, indicated with the prefix "`pX_track_tc`", specify the relative time in units of hour-minute-second with respect to the starting end of a track. The starting end of the track of a particular path is defined as hour 0, minute 0 and second 0. Similarly, the path time codes, indicated with the prefix "`pX_path_tc`", specify the relative time in units of hour-minute-second with respect to the starting end of a path. The starting end of a particular path is defined as hour 0, minute 0 and second 0.

A `path_descriptor()` area as detailed above is provided in the PSM of the entry sector and includes time codes for each path. An illustration of the `path_descriptor()` is shown



in Fig. 6B. By storing the time code for each of the different paths in each entry sector, the exact elapsed time of reproduction of a particular path can be accessed from the `path_descriptor()` and displayed to the user concurrent with data reproduction and display. An accurate time indication is given for each particular path even though certain sections of data may be common to different paths. In an analogous manner, track numbers for each path may be included in the `path_descriptor()` area in the PSM of the entry sector.

Alternatively, a time code may be assigned, preferably consecutively, to each entry sector and stored in the `time_code_descriptor()` area of the particular entry sector as illustrated in Fig. 6C. A time code assigned in this manner may be used for searching scene indexing information and identification information. In an analogous manner, a track number may be assigned, preferably consecutively, to each entry sector and stored in an area of the particular entry sector, for example in a `track_number_descriptor` area.

When a video program is played, so-called trick modes are often used. The video signal may then be displayed in fast forward or in reverse mode. In the case of an MPEG-2 signal, always a number of sectors are skipped in such trick modes. In order to have this possibility also in a specific path, there is given in `pX_sectors_to_read` (in Fig. 5 arrow 56) how many sectors of the present section are yet to follow

before the end of the section and, for the reverse mode, in `pX_sectors_from_start` (Fig. 5 arrow 55) how many sectors precede in the section. If the segment does not form part of the respective path, this may be denoted by a given value, for example, 0. In such case the `path_descriptor` for that path could also be omitted, but no address of a direct jump to a section of the video material that does belong to the selected path will then be available.

For a jump from the end of a section to the consecutive section, the distance to this section is denoted as `pX_offset_next_section`, in Fig. 5 arrow 54. With the last section of a path, a predetermined value may be given, for example, `pX_offset_next_section=0`. For a jump to the previous section in the case of reverse mode, the distance is given in `pX_offset_previous_section`, in Fig. 5 arrow 53. The last entry point in the previous section is then taken as the destination. The first section may be indicated by a predetermined value. Needless to observe that in another embodiment the first and last sections are indicated by separate flags. Alternatively, it is possible to include the path information in a descriptor not for each path but in a combination for all sorts of paths.

As stated above, it is customary to subdivide such programs for the user into tracks. The user can then rapidly obtain a survey of the course of a program and, if so

desired, can jump to another part. A player will often know the operating functions "next" and "previous" for this purpose, or have a direct track number selection. In Fig. 5 the track numbers for the selected path 34 are referenced T4, T5, T6 and T7. Furthermore, there should be observed that the boundaries of a track generally do not coincide with the section boundaries, since violent or other selective scenes may occur anywhere in the program. In the given path 34 there is a jump to, for example, track T7 in section 0, but for another path the transition from T6 to T7 may lie in the area between sections N and 0. In the path\_descriptor shown in Fig. 6 there is a direct jump address present in pX\_offset\_next\_track, so that a jump to the proper entry point of the next track along the respective path is possible in a simple manner from any point, denoted in Fig. 5 by arrow 59. For a previous jump, the address is given in pX\_offset\_previous-track, in Fig. 5 arrows 57 and 58. In Fig. 5 the jump to a previous track for the first entry point of a section is denoted by arrow 57; at the further entry points is given the beginning of the actual track shown in arrow 58. The user may then jump back to the beginning of the present track and from there further back, if desired.

In a further embodiment of the information carrier there is also a descriptor present, similar to Fig. 6, for other information related to the video program, such as audio

or subtitles, which descriptor indicates for which paths a certain stream is suitable. The descriptor contains, for example, a flag for each path. For example, with the same video material, bad language may be replaced by more acceptable language. In another path are then included the same video sections, but with a separate audio stream and/or subtitle stream, in which flags then indicate which stream is to be used for a selected path. The separate audio or subtitle stream may be present during the whole video program. The separate audio and/or subtitle stream, however, is only necessary during the sections in which it is used. During the rest of the video program they may be omitted. The playback device must then comprise means for selecting for each individual segment the audio and/or subtitle stream that belongs to the selected path. In another embodiment, parallel video streams may be included in which a similar arrangement of the descriptor with a flag for each path is then possible. This could be used, for example, for including various camera angles with the same audio and subtitles.

Fig. 7 diagrammatically shows a possible structure of Tables Of Contents of an information carrier according to the invention. In a Disc Table Of Contents (D\_TOC) 70 can be found information which is valid for the whole disc. This relates, for example, to a name of the whole disc and data

about the origin. This Table Of Contents also includes a Table 71 containing data about the classification. This Table gives a number of classification or rating levels customary in a specific country, in the language of that country and links thereto a definition\_number. For example, 0 then denotes "no rating" and the number increases with the rating level. D\_TOC is also an indication of the number of video programs on the information carrier and of the references to the respective Program Tables Of Contents (P\_TOC) 72 indicated by lines 75. P\_TOC includes, for example, information about the paths in one or more path\_tables 74, so that this path information is thus easily locatable, as was described with reference to Fig. 3. The P\_TOC 72 also includes a Table 73 in which a rating\_definition number is given to the respective program per country and per path, which number corresponds to a definition number defined in the D\_TOC 71. Also a name for the respective program is included per path and per country, so that the various possible versions may be distinguished by the user. In this manner, the name and the rating of a specific version of a video program can be given in the language country to which the playing device is set. It is also possible to block rating levels starting from a certain level in the player, so that the parents can allow their children to watch only video programs up to a specific

rating. They can then utilize the indications customary in their country. However, it is still the responsibility of the supplier of the video program to assign the correct rating levels and record them on the information carrier in Table 73.

The described way of classifying the rating levels is only an example. Another embodiment of a rating system is, for example, assigning a rating directly for each path. The weight of the rating codes is established beforehand. It is also possible to include one or more classification codes per segment, which codes denote the weight of the whole, or the weight for each category, such as sex or violence. When a next section is selected, the user-selected preferences on the player can then be taken into account.

As denoted by lines 75 in Fig. 7, it is possible to record a plurality of video programs on an information carrier. Customarily, an information carrier is subdivided into tracks which have an (absolute) track numbering, for example, starting from 1. However, to a user it is annoying if the subdivision into tracks counts on during the various programs. The third program could then start, for example, at track 29. Therefore, it is attractive to apply relative track numbers starting from 1 to each video program. If so desired, it is also possible to make different track subdivisions per path.

In an embodiment of the information carrier, the D\_TOC 70 includes a Table stating for each available path a list of initial and final addresses, a last entry point, a playtime and a final system time of each track. It also includes for each track a track number and a program number, so that the assignment of the track number within each program is completely free. The user can then jump directly to a specific track of a specific program.

Another option is to include program linkage information in the D\_TOC 70, which contains for each of the possible paths, for example, for each program, the first track number, the last track number and the addresses of these tracks. As a result, the user may be shown the total number of tracks in the version of the video program selected by him. It is also possible for the user to jump directly from one video program to a next video program.

In an embodiment of the information carrier, a relation from the first track of the video program to an absolute track number into which the information carrier as a whole is subdivided, can be established in D\_TOC 70 or P\_TOC 72. For example, an offset which is to be added to the relative track number to obtain the absolute track number, is to be included for this purpose. Track boundaries of relatively numbered tracks are then to be equal to track boundaries of absolute tracks.

In another embodiment, the P\_TOC 72 includes a Table of track information. For each available path are included initial and final addresses per track, a last entry point, a playtime, an end-of-system-time and a track number, so that the assignment of track numbers is again completely free. The P\_TOC 72 also includes the number of tracks per path for each program. The track subdivision is completely independent of the track subdivision of further video programs. Another option is to let a Table have a track number for each consecutive segment of a specific section.

In another embodiment, track information is embedded in the video stream, for example, included in the path information as described with reference to Figs. 5 and 6. In Fig. 6, track\_number is the track number for the respective path valid for the selected version of the respective video program. Via this facility the user can be simply shown a track numbering in his version of the video program. As denoted by arrows 57, 58 and 59, also jump addresses to subsequent and previous tracks and the beginning of the actual track are embedded in the video stream.

Fig. 8 shows a device for reading an information carrier 1 according to the invention such as, for example, a Multi Media Compact Disc (MMCD). The device comprises scanning means 80 for scanning the track 21 by an optical beam. A description of similar reading of a CD may be found



back in the title mentioned with reference to Fig. 2. The scanned signal goes to means 81 to be demodulated and error corrected. From there the signal goes to a buffer 82 where a monitoring signal 88 is generated indicative of the degree of fill. The control means 84 displace and focus the scanning means 80 for reading the desired sectors from the information carrier 1. The monitoring signal 88 goes to the control means 84 which, as required, read picture information from the information carrier to maintain a sufficient degree of fill for the buffer 82. As a result, the video and audio signal are continued as uninterruptedly as possible during jumps. The information signal from buffer 82 goes to a decoder 83 for the reproduction of the video signal on output 86 and the audio signal on output 87. The information signal also goes to means 85 for the recovery of the path information. The means 85 receive through an input 89 information about the path to be selected. This may be manually selected directly by the user on the basis of the available versions, or a specific permitted rating level may be set on the player (for example, by the parents), which can only be deviated from after a code has been keyed in. The path information is read out prior to the reproduction of the video program and stored in a memory, or, each time when path information is necessary, read directly from the file on the information carrier. After a section has been read

completely, the consecutive section will have to be known to the means 85. The path information is indicative of sections to be displayed consecutively, as described with reference to Figs. 3 to 6. Jump instructions are derived therefrom and passed on to the control means 84. Once the jump has been completed, further picture information is read from the buffer 82. During the jump, no new picture information reaches buffer 82 for a while, but the picture display may continue uninterruptedly as a result of the information still present in the buffer. As a result, a continuous series of consecutive sections is displayed along a path as indicated by the path information.

If the buffer 82 contains insufficient video information for bridging the jump, it is possible to show on a display (for example, the TV screen) the (estimated) period of time that is necessary for reaching the next section to be displayed. If so desired, it is possible to show a diminishing time value, an hourglass, or shrinking time bar. If one only needs to wait for a brief period of time, it is also possible to show the last image of the present section on the picture screen as a still picture until the new section is displayed.

In an embodiment of the reading device, the playtime of the video program can be shown to the user, for example, on the picture screen or on a separate display. For this

purpose, means 85 are adapted for recovering the playtime information of the information carrier, so that the playtime of the program or of the track is shown for the selected path.

In an embodiment of the reading device, an information carrier having a picture signal with entry points is used as described with reference to Fig. 5. The means 85 then recover the control information multiplexed with the video stream and then recover the path information from this control information. In the reverse mode, addresses of segments preceding the actual section are used for determining the jump addresses. It is also possible to show the time elapsed per path or per track, if the information carrier contains the respective time codes.

In other embodiments of the reading device, a buffer 82 which is present, for example, on an analog video disc, is absent. In that case, there are brief interruptions of the video and audio signal. A reading device can either comprise a decoder 83 of its own, or the information signal may be applied to a decoder in another display device. In another embodiment, the reading device comprises a picture screen on which the picture is displayed directly.

Fig. 9 shows a device for providing information carriers of said type, such as a CD or a MMCD. Firstly, a master information carrier 97 is made by said device. From

this master information carrier 97 are then produced a multiplicity of information carriers by a customary process of moulds and presses (not shown). The picture information is applied to the picture encoder means 93; tile video information through an input 90 and the audio information and further information through a separate input 91. The picture encoder means 93 code the video information and the further information and generate the information signal. Information about sections, classification codes and paths to be selected is applied through input 92 to path information generator means 94 which add the path information described with reference to Figs. 3 to 6 to the coded picture information. The channel coding unit 95 codes the information signal in a manner customary for the disc-shaped carrier and passes it on to a write unit 96. Write unit 96 writes, for example, by a high-intensity laser beam, the coded information signal on the master information carrier 97. A customary type of system controller (not shown) provides a control of the speed of rotation of the disc and the positioning of the write unit over track 21 to obtain the desired pit and track density. For a further description of the CD system, reference be made to Fig. 2 of said title.

In another embodiment, a similar device is suitable for recording the information signal on an information carrier which can be played back forthwith, such as a CD recordable.

Another embodiment of this is, for example, a device for writing and reading a VCR tape or an optical tape. In a further embodiment it is possible to add the path information at a later stage, for example, for making various versions of a home video. The complete basic program has then been recorded previously and the path information is determined afterwards and added, for example, in a separate file.

Fig. 10 illustrates a preferred format for the recording of information on an information carrier according to the present invention. As shown, the format includes a primary volume descriptor area (PVD), a disc table of contents recording area (D\_TOC), multiple program table of contents recording areas (P\_TOC1, P\_TOC2, P\_TOC3), and multiple program information recording areas (PRG1, PRG2, PRG3,...PRGN). In the PVD area, primary volume descriptors, defined pursuant to ISO 9660, are recorded. An exemplary implementation of ISO 9660 is illustrated in Fig. 11.

A preferred syntax for a D\_TOC area is illustrated in Fig. 12. A D\_TOC area stores information regarding the contents of the information carrier. For example, the rating codes may be stored in the rating\_definitions() area of a D\_TOC area. Preferably, the rating\_definitions() area include areas for storing the number of countries defining the rating (num\_of\_countries), a 2-byte country code (iso\_country\_code) as defined in ISO3166, a number of

definition of the rating (`num_of_definition`), a number specifying the rating type (`rating_type_number`), and a letter string for specifying the rating type (`rating_type_string`) as defined in ISO646. Optionally, the syntax for a D\_TOC area may omit a `rating_definitions_offset` area.

As illustrated in Fig. 12A, the `disc_tracks()` area may include areas for storing the number of tracks (`number_of_tracks`), program number (`program_number`), track number (`track_number`), logical sector address of track starting (`start_lsa`), logical sector address of the last sector of the track (`last_lsa`), and the logical sector address of the last entry sector in the track (`start_es_lsa`).

A preferred syntax for a P\_TOC area is illustrated in Fig. 13. A P\_TOC area stores information regarding the contents of the information carrier in a specific recorded PRGx area. Program information for each program 1,2,...N is recorded in a corresponding program information recording area (PRG1, PRG2, PRG3,...PRGN). The program information for each program is divided into packets of program data. For example, `path_rating_assignments()` areas, `program_tracks()` areas, `entry_points()` areas, and `path_table()` areas are included in a P\_TOC area.

In `path_rating_assignments()` areas, areas are defined for a number of countries defining the rating (`num_of_countries`), a 2-byte country code (`iso_country_code`)

as defined in ISO3166, and a letter string for specifying the path name (path\_name) as defined in ISO646. The location of specific entry points may be stored in the P\_TOC area to facilitate the selective reproduction of sections of the recorded program to form different versions comprising different sequences of recorded sections.

As illustrated in Fig. 13A, the program\_tracks() area includes areas for the total number of tracks employed in each path defining the reproducing sequence (number\_of\_path\_tracks), track number (track\_number), relative sector address of track starting (start\_rsa), relative sector address of the last sector of the track (last\_rsa) and the relative sector address of the last entry sector in the track (start\_es\_rsa). A relative sector address ("rsa") may be determined relative to the beginning of the program. For example, the beginning of a program may be assigned an address of zero.

As illustrated in Fig. 13B, the path\_table() area includes areas for the number sections in the path (number\_of\_sections), the relative sector address of the first entry sector of the section, and the relative sector address of the last entry sector in the section (last\_es\_rsa).

Fig. 14 illustrates an example of the formation of different versions of a program by selectively reproducing

different sequences of recorded sections of program information. Each version is produced by following a particular "path" which indicates the sequence of recorded sections that comprises the particular version of the program. According to the illustrated path 0, a program version is formed from a single section of program data which extends from a starting segment to an ending segment and includes a starting entry point and an end point. To facilitate explanation, each of paths 0, 1, 2 and 3 are shown to share a common pair of starting and ending segments; the sharing of certain segments among different versions is not required.

In path 1 of Fig. 14, a program version is formed from two sections of recorded data wherein the start of each section is designated by an entry point and the end of the version is designated by an end point. As shown, the version defined by path 1 differs from that of path 0 in that a portion of data included in path 0 is not included in path 1. In path 2, a program version is formed from three sections of recorded data wherein the start of each section is designated by an entry point and the end of the version is designated by an end point. As shown, the version defined by path 2 differs from that of path 0 in that path 2 includes a portion of data not included in path 0, specifically the second section of path 2.



In path 3, a program version is formed from five sections of recorded data wherein the start of each section is designated by an entry point and the end of the version is designated by an end point. As shown, the version defined by path 3 differs from that of path 0 in that path 3 includes two portions of data not included in path 0, specifically the second and forth sections of path 3, but omits a portion of data included in path 0.

Placement of a complete access unit, such as an audio frame, an I-frame, a P-frame, or a B-frame at the beginning and end of each section facilitates "jumping" of the reproduction operation from one section to another allowing the uninterrupted reproduction of at least one of the video data or the audio data.

If at least one path, for example path 0, is comprised of only one section and is free of "jumps" then it may be reproduced with a simplified reproduction system not designed for "jumping".

In the MPEG system proposed in ISO/IEC JTC1/SC29/WG11, video data and audio data are divided into packets to form a video packet stream, also referred to as a "video packetized elementary stream," and an audio packet stream, also referred to as an "audio packetized elementary stream." The two streams are time-division multiplexed to produce a program stream. The elementary stream of the program stream is

defined in a program stream map. The program stream is further processed for storage on an information carrier.

Fig. 15A illustrates a preferred embodiment of the program stream. As shown, the program stream comprises a system header and at least one PES packet. According to the MPEG standard, the program stream includes a system layer and a compression layer. A pack layer and a packetized elementary stream (PES) constitute a system layer. Each multiplexed bitstream comprises one or more packs. Each pack includes at least one PES packet or a program stream map.

Typically, a pack comprises a header which includes areas for a pack-start-code, a system clock reference (SCR) or a program-mux rate, and a number of PES packets. Preferably, the pack-start-code is the 32-bit code 0x000001B4 (hexadecimal notation).

Fig. 15B illustrates the structure of a PES packet, while Figs. 16A, 16B, 16C and 16D, together show a preferred syntax for the PES packet. As shown, a PES packet includes a PES packet header and accompanying packet data. A PES packet header includes areas for a packet-start-code-prefix, a stream id, a PES-packet-length, and an optical-PES-header. The optical-PES-header includes a presentation time stamp (PTS) and a decoding time stamp (DTS). Preferably, the packet-start-code-prefix is the 24-bit code 0x000001 and the stream-id is an 8-bit code representing the length of a

succeeding packet. PES-packet-length may vary up to a maximum of 2048 bytes. Preferably, packet data may be video data, corresponding to a video stream, or audio data, corresponding to an audio stream.

Advantageously, the above-described definition of pack and packet facilitates reproduction of multiplexed data from any sector of the information carrier on a random access basis.

In accordance with the above, an entry point, implemented as an entry packet, may be described with two packets, a PSD packet and a PSM packet. In a PSD packet, the program stream directory (PSD) describes the current directory offset (previous directory offset) of the current PES packet. The PSD further includes the distances between the current PES packet and up to six neighboring entry points (three before and three after). The syntax and layout of a PSM packet is illustrated in Figs. 22A and 22B. The PSM defines the elementary stream of the program stream, for example, the PES data type such as MPEG-video, MPEG-audio or the like is defined. The descriptor() area defined in the PSM packet may include a variety of descriptors including path\_descriptor or program\_descriptor.

In another implementation of the MPEG system defined in ISO11172 and illustrated in Fig. 17, each multiplexed bitstream is comprised of one or more packs and one

ISO\_11172\_end\_code. An ISO\_11172\_end\_code is preferably the 32-bit code 0x000001B9 (hexadecimal notation). Each pack includes a header and one or more packets. The header includes a pack\_start\_code, preferably the 32-bit code 0x000001B4, and a system clock reference (SCR). Each packet includes a packet\_start\_code\_prefix, a stream\_id, a packet\_length, a presentation time stamp (PTS), a decoding time stamp (DTS), and packet data. Preferably, the packet\_start\_code\_prefix is the 24-bit code 0x000001. The stream\_id represents the type of packet and the packet\_length (16 bits) represents the succeeding packet length. This arrangement allows audio and video data to be multiplexed.

Fig. 18 illustrates a multiplexed bitstream format which includes entry points. The format comprises, in order, a pack header, a video\_packet\_header, video data, an entry point, a video\_packet\_header, video data which includes an I-frame, an audio\_packet\_header and audio data. A program stream directory (PSD) and a program stream map (PSM) are included in the entry point which is implemented as an entry packet. It should be noted that the entry point is positioned before the video\_packet\_header which immediately precedes the I-frame.

A sector having both the PSD and PSM recorded therein is referred to as an "entry sector."

A data recording device implementing the above-described data formats is illustrated in Fig. 19. The recording device, indicated generally at 1900, receives audio and video input, packets the audio and video input, time-division multiplexes the packets, and records the stream of multiplexed packets on an information carrier. Recording device 1900 includes an audio encoder 1902, a video encoder 1904, a multiplexing unit 1906, a storage medium 1908, a table of contents (TOC) data generating circuit 1910, a table of contents (TOC) appending circuit 1912, a sector header appending circuit 1914, an error correction code (ECC) encoder 1916, a modulation circuit 1918 and a cutting machine 1920. Although shown in connection with a disk 1922, recording device 1900 may record data to any information carrier including, for example, a magnetic tape or disk, a magneto-optical disk, an optical disk, or a semiconductor memory.

Audio encoder 1902 and video encoder 1904 are conventional signal encoders which, for example, may perform compression encoding. Multiplexing unit 1906 multiplexes the encoded audio and video data and determines the locations of entry points in the data. A preferred embodiment of multiplexing unit 1906 is discussed below in connection with Fig. 20.

Storage medium 1908 stores multiplexed encoded audio and video data and may comprise any conventional data storage medium. Preferably, storage medium 1908 is a digital storage medium comprising a disk drive for reading to and writing from a magnetic disc, a magneto-optical disk or an optical disk.

TOC data generating circuit 1910 generates TOC data as a function of entry point information. TOC appending circuit 1912 appends TOC data to multiplexed data. Sector header appending circuit 1914 divides data into sectors and appends a header to each sector. ECC encoder 1916 is a conventional error correction code encoder for appending error correction codes to data.

Modulation circuit 1918 is a conventional signal modulator for modulating a signal suitably for utilization by cutting machine 1920. Cutting machine 1920 is a conventional data recording device for recording data on an information carrier.

In operation, video signals are supplied through the video input to video encoder 1904 and audio signals are supplied through the audio input to audio encoder 1902. Video encoder 1904 supplies encoded video signals to multiplexing unit 1906. Audio encoder 1902 supplies encoded audio signals to multiplexing unit 1906. Multiplexing unit

1906 supplies multiplexed encoded audio and video data to storage medium 1908 for temporary storage.

Multiplexed encoded audio and video data from storage medium 1908 are supplied to TOC appending circuit 1912 which appends TOC data to the multiplexed bitstream. The TOC data includes entry point information, e.g. sector addresses, regarding entry points in the multiplexed data and is supplied to TOC appending circuit 1912 by TOC data generating circuit 1910. The TOC data is generated by TOC data generating circuit 1910 from entry point data supplied from multiplexing unit 1906.

The multiplexed bitstream, incorporating TOC data, is supplied to sector header appending circuit 1914 which divides the bitstream into data sectors appropriately sized for storage in sectors of an information carrier. It is preferred that the bitstream is divided into 2048 byte sectors for storage in corresponding physical sectors of an information carrier. A sector header, preferably comprising 16 bytes and indicating the sector number of that sector, is appended to each sector of data. A pack or packet header is placed at the beginning of each sector.

The sectors of data are then supplied to ECC encoder 1916 which appends error correction codes, such as parity codes, to the sectors of data. The sectors of data, augmented with error correction codes, are supplied to

modulation circuit 1918 for modulation to produce a modulated signal. The modulated signal is supplied to cutting machine 1920 for recording on disk 1922.

Fig. 20 illustrates a preferred embodiment of multiplexing unit 1906. As shown, multiplexing unit 1906 includes a video entry point detecting circuit 2002, code buffers 2004 and 2006, a switching circuit 2008, a header appending circuit 2010, an entry point generating circuit 2012, a controller 2014, a multiplexed system clock generating circuit 2016, an entry point storing unit 2018, and a rating appending circuit 2020. Also shown is a switch 2024 and a local decoder 2022.

Video entry point detecting circuit 2002 detects the presence of I-frames in the encoded video data supplied from video encoder 1904 and generates an entry point generating signal in response to each occurrence of an I-frame. Alternatively, video encoder 1904 is coupled directly to controller 2014 and generates an entry point generating signal each time an I-frame is encoded while video entry point detecting circuit 2002 is omitted.

Code buffers 2004 and 2006 and entry point storing unit 2018 are conventional data storage devices. Switching circuit 2008 is a conventional controlled switching device. Controller 2014 may comprise a microprocessor-based device.



Multiplexed system clock generating circuit 2016 generates a system clock signal.

Rating appending circuit 2020 generates a path-descriptor for the current entry point. A programmer programs the rating appending circuit 2020 for each section that is incorporated into the reproduction sequence of a particular path and determines the section boundaries. Optionally, a switch 2024 (shown) is coupled to rating appending circuit 2020 and a local decoder 2022 (shown) is coupled to storage medium 1908 and to controller 2014. Switch 2024 and local decoder 2022 may be omitted as appropriate.

Encoded video signals are supplied by video encoder 1904 through video entry point detecting circuit 2002 to code buffer 2004. Encoded audio signals are supplied by audio encoder 1902 to coder buffer 2006. The output of buffer 2004 is coupled to terminal E1 of switching circuit 2008. The output of buffer 2006 is coupled to terminal E2 of switching circuit 2008. The output of entry point generating circuit 2012 is coupled to terminal E3 of switching circuit 2008. Output terminal F of switching circuit 2008 is coupled to header appending circuit 2010. Multiplexed audio and video data and header information, including specifically PSD and PSM information, is supplied from header appending circuit 2010 is supplied to storage medium 1908.

Controller 2014, responsive to the system clock signal, controls switching circuit 2008 to sequentially and periodically couple input terminals E1 and E2 to output terminal F. In this manner, encoded data is supplied from buffers 2004 and 2006 to header appending circuit 2010. Controller 2014 controls switching circuit 2008 to complete an access unit, such as an audio frame, and I-frame, a P-frame, or a B-frame at the jump point. This will be described in detail below in connection with Figs. 23A, 23B, 24A and 24B.

Circuit 2010 is controlled by controller 2014 to generate an MPEG-type bitstream from the encoded data. Specifically, header appending circuit is controlled to append a video packet header to video data supplied from buffer 2004 and to append an audio packet header to audio data supplied from buffer 2006.

Controller 2014 receives the entry point generating signal and, in response, controls entry point generating circuit 2012 to supply a program stream directory and a program stream map to input E3 of switching circuit 2008. Controller 2014 controls switching circuit 2008 to insert the PSD and PSM directly before the video entry point (I-frame) by appropriately controlling the timing of the coupling of input terminal E3 with output terminal F. In this manner,

the PSD and PSM are supplied to header appending circuit for multiplexing with the encoded audio and video data.

In the PSD of each entry point, the locations of the three entry points located immediately adjacent but before the respective entry point are stored in three prev\_directory\_offset areas. The locations of the three entry points located immediately adjacent but after the particular entry point are also stored in the PSD in three next\_directory\_offset areas. However, since the locations of future entry points may not be determined until such points are processed, such storage is deferred until the three succeeding entry points have been processed. Accordingly, controller 2014 controls entry point storing unit 2018 to store the location of each entry point. Actual storage of the entry point locations in each of the PSDs occurs following the storage of the multiplexed audio and video data in storage medium 1908.

After the video and audio data have been multiplexed and stored in storage medium 1908, controller 2014 accesses the location information stored in entry point storing unit and routes the location information to storage medium 1908. For each of the entry points stored in storage medium 1908, the locations of the three entry points after the particular entry point and the locations of the three entry points before the particular entry point are supplied from entry

point storing unit 2018 to storage medium 1908 for storage in association with that particular entry point. Entry point storing unit 2018 also supplies entry point information to TOC data generating circuit 1910. In an alternate embodiment, actual storage of the locations of the three entry point preceding a particular entry point occurs concurrent with the storage of the multiplexed data.

Fig. 21 illustrates another embodiment of a data reproducing device 2100 according to the present invention. Data reproducing device 2100 is comprised of tracking servo circuit 2102, pickup 2104, drive control circuit 2106, demodulation circuit 2108, error correction code (ECC) circuit 2110, header separation circuit 2112, switch 2114, video decoder 2116, audio decoder 2118, controller 2120, entry point storing unit 2122, and TOC storing unit 2124.

Pickup 2104 is a conventional pickup device for reading information from an information carrier. Preferably, pickup 2104 comprises an optical pickup for optically accessing data recorded on an optical disk. Similarly, tracking servo circuit 2102, drive control circuit 2106, demodulation circuit 2108, and error correction code circuit 2110, are conventional devices.

Entry point storing unit 2122 and TOC storing unit 2124 are conventional data storage devices. Switch 2114 is a

conventional controlled switching device. Controller 2120 may comprise a microprocessor-based device.

In operation, controller 2120 issues a control signal to drive control circuit 2106 to read the leading sector on information carrier 1922. Drive control circuit 2106 drives pickup 2104 by means of tracking servo circuit 2102 to initiate reproduction of data from the leading sector on information carrier 1922. Pickup 2104 reproduces data from information carrier 1922 and supplies the reproduced data to demodulation circuit 2108. Demodulation circuit 2108 demodulates the reproduced data and supplies demodulated data to ECC circuit 2110 for error correction.

ECC circuit 2110 detects and corrects errors found in the reproduced data and supplies the error-corrected data to header separation circuit 2112. Header separation circuit 2112 separates TOC information from the error-corrected data and supplies the TOC information to controller 2120. Controller 2120 stores the TOC information in TOC storing unit 2124 and displays the TOC information to a user by means of a display unit (not shown).

In response to user input, controller 2120 issues a control signal to drive control circuit 2106 to initiate a reproduction operation. Drive control circuit 2106 drives pickup 2104 by means of tracking servo circuit 2102 to a position on the information carrier 1922 selected by the

user. Controller 2120 also issues a control signal to video decoder 2116 and to audio decoder 2118 in preparation for data decoding. In accordance with the process described above, data is reproduced from the information carrier, demodulated, and error-corrected. The error-corrected data is supplied to header separation circuit 2112. Position information regarding the current position on information carrier 1922 from which data is being reproduced is supplied by drive control circuit 2106 to controller 2120.

From the error-corrected data, header separation circuit 2112 separates the pack header, packet header, program directory, program stream directory (PSD), and program stream map (PSM) and supplies such header data to controller 2120. The time-division multiplexed data which remains is supplied to input terminal G of switch 2114. Output terminal H1 of switch 2114 is coupled to an input of video decoder 2116 while output terminal H2 is coupled to an input of audio decoder 2118.

Controller 2120 stores entry point information included in the header data in entry point storing unit 2122. Along with each entry point is stored the location of the point as determined from the current position information supplied by drive control circuit 2106. The relative location of the entry points with respect to one another may also be stored.

Controller 2120 controls switch 2114 to sequentially couple input terminal G with either output terminal H1 or H2 in accordance with the stream\_id included in the corresponding packet header. The time-division multiplexed data is thus selectively routed to either video decoder 2116 or audio decoder 2118, as appropriate.

In a reproduction operation, controller 2120 retrieves from TOC storing unit 2124 rating information stored in the rating\_definition() area of the D\_TOC area. Controller 2120 causes the display unit to display a list of countries having the particular rating definition and corresponding to the country code stored as part of the rating information. From this list, a user selects the appropriate country, e.g. the country in which the data is to be reproduced. The user enters the selection through a user interface, not shown, which transmits the user's selection to controller 2120. For example, the user interface may comprise an operating button located on reproducing device 2100 or a remote control device for controlling reproducing device 2100.

Following receipt of the user's selection of a particular country, controller 2120 controls the display unit to display a list of corresponding rating\_type\_number information and rating\_type\_string information. The user indicates the rating\_type\_number information which are to be allowed for reproduction and enters the selection into the

user interface. The user interface transmits the user's selection to controller 2120. Following receipt of the user's selection of allowable rating\_type\_number information, controller 2120 retrieves path\_rating\_assignments() information included in P\_TOC information from TOC storing unit 2124.

As a function of the country code and rating\_type\_number information selected by the user, controller 2120 determines from the path\_rating\_assignments() information the path\_name information of an allowable path of reproduction. If only one path is determined to be allowable, reproduction according to that path is commenced by controller 2120.

If multiple paths are determined to be allowable, controller 2120 controls the display unit to display rating\_type\_string information and path\_name information corresponding to the selected rating\_type\_number information. The user then selects among the path\_name information and corresponding rating\_type\_string information for the path which is desired for reproduction and enters the selection into the user interface. The user interface transmits the user's selection to controller 2120 which controls reproducing device 2100 to reproduce the selected version of the video work according to the selected path. By the above-described process, a user selects among plural versions of



a video work to select the version that has a rating which is consistent with the user's preference.

Alternatively, if multiple paths are determined to be allowable, controller 2120 may commence reproduction according to the path corresponding to the smallest path\_number information. As a further alternative, a default path may be pre-recorded on the information carrier which is retrieved by controller 2120 which then commences reproduction according to the default path information. Preferably, such default path information is stored as path\_rating\_assignments information. Optionally, a default path may be pre-stored in controller 2120.

In an alternate embodiment, reproducing device 2100 includes an input device (not shown), such as a switch, which may be set by a user to indicate the rating\_type\_number information which reflects the user's preferences. Controller 2120 accesses the user's preferences from the input device and initiates reproduction of the video work version that has a rating consistent with the user's preferences. The input device maintains the user's selection for future use by reproducing device 2100. Optionally, the input device may be positioned so as to be inaccessible to minor-aged persons, constructed so as to be too complicated to be operated by minor-aged persons, or otherwise locked to

prevent or at least to deter reproduction of certain version of a video work.

In another alternate embodiment, rating\_type\_string information and path\_name information, based upon rating\_definition() information or path\_rating\_assignments() information, for every version of a video work recorded on the information carrier is displayed to the user by means of a display unit (not shown) controlled by controller 2120. Such an embodiment enables a user to choose from among all versions of the video work that are available on the information carrier.

In a reproducing operation, controller 2120 receives a command from a main controller (not shown) to enter into a rating mode. In rating mode, controller 2120 monitors data flowing through header separating circuit 2112. If a PSM is detected, controller 2120 monitors the data for a path descriptor. If no path descriptor is detected, straightforward data reproduction occurs.

Fig. 23A illustrates completed access units on both sides of a jump point located between two sectors. Fig. 23B illustrates uncompleted access units on both sides of a jump point located between two sectors. Fig. 24A illustrates an arrangement of video data in which prediction or reference for decoding a portion of data need only be made with respect to data on the same side of a jump point as the data to be

decoded. A video encoder 1904 which does not perform prediction or reference across a jump point for decoding access units may be utilized if data is arranged as shown in Fig. 24A. Fig. 24B illustrates an arrangement of video data according to which the decoding of certain data on one side of a jump point will necessitate prediction or reference with respect to data located on the opposite side of the jump point.

Fig. 25 illustrates a data format according to the invention produced when plural data sequences, that is paths, are recorded on the information carrier. As shown, the bitstream in the recording medium has its path constituted by three sections S1, S2 and S3 which are separated by two unused portions of the information carrier. Reproduction of a version of the program constitutes reproduction of sections S1, S2, S3 in order. Section S1 is recorded on tracks 1 and 2, section S2 is recorded on tracks 2 and 3, and section S3 is recorded on tracks 3 and 4.

In a straightforward reproduction operation, controller 2120 controls data reproduction to commence at the leading end of the first section which is presumed to be recorded in the first section S1. Controller 2120 detects the program stream map (PSM) stored in the entry point recorded in the first section S1 and detects the `path_descriptor()` associated with the path to be reproduced from the `path_descriptors()`

area. Controller 2120 stores the path\_descriptor information in entry point storing unit 2122. Plural path\_descriptors may be present in each path of the PSM.

The information of pX\_sectors\_to\_read, indicated by arrow 26<sub>1</sub>, pX\_sectors\_from\_first, indicated by arrow 26<sub>2</sub>, pX\_offset next\_section, indicated by arrow 26<sub>3</sub>, pX\_offset\_previous\_section, indicated by arrow 26<sub>4</sub>, pX\_offset\_next\_track, indicated by arrow 26<sub>5</sub>, and pX\_offset\_previous\_track, indicated by arrow 26<sub>6</sub>, are included in path\_descriptor information, as explained above and illustrated in Figs. 26A, 26B and 26C.

After storing the path\_descriptor() information, controller 2120 compares the sector address of the sector currently reproduced from the drive control circuit 2106 to the sector address stored in entry point storing unit 2122, as indicated by arrow 26<sub>1</sub> in Fig. 26A. When the end point of the first section S1 is reached, shown at the tip of arrow 26<sub>1</sub> in Fig. 26A, the controller 2120 controls the drive controlling circuit 2106 to access the start position of the next section. Accordingly, reproduction is started from the leading end of the second section S2, indicated by arrow 26<sub>3</sub> in Fig. 26A.

After starting reproduction from the leading end of the second section S2, controller 2120 detects in the PSM of the entry point recorded in the second section S2 the

path\_descriptor information associated with the path to be reproduced, and causes the detected path\_descriptor information to be stored in storing unit 2122.

After storing the path\_descriptor information, the controller 2120 compares the sector address of the sector currently reproduced by drive control circuit 2106 with the end address stored in entry point storing unit 2122, indicated by arrow 26, of Fig. 26B. Reproduction of the second section continues until the end as indicated by arrow 26, in Fig. 26B. When the reproduction of the second section S2 comes to a close, controller 2120 controls drive control circuit 2106 to access the start position of section S3, as indicated by arrow 26, in Fig. 26B. Reproduction continues at the leading end of section S3.

After starting reproduction at the leading end of section S3, controller 2120 detects in the PSM of the entry point recorded in the section S3 the path\_descriptor information corresponding to the path to be reproduced and stores the information in entry point storing unit 2122.

In section S3, pX\_offset\_next\_section will contain a zero value indicating that a next section is not present. Accordingly, controller 2120 allows reproduction of section S3 to proceed to the end of the section, as shown by arrow 26, in Fig. 26C, before reproduction is terminated.

Thus, reproduction of plural sections occurs as described above in accordance with the information stored in the path\_descriptor areas of the sections.

An example of a fast forward (FF) reproduction operation according to the invention is described in the following. If fast forward reproduction is commanded during reproduction of section S1 and the path\_descriptor information recorded in section S1 has not yet been stored in the entry point storing unit 2122, controller 2120 detects the path\_descriptor information associated with the path to be reproduced from the PSM of an arbitrary entry point in section S1, and that path\_descriptor information is stored in storing unit 2122.

Controller 2120 controls device 2100 to sequentially access the recorded entry points in accordance with the location information regarding forward and backward adjacent entry points stored in the PSD and to reproduce the I-picture placed directly after the access entry point. The sector address of the entry point being accessed is compared to the sector address indicated by arrow 26<sub>1</sub> of Fig. 26A stored in the entry point storing unit 2122, and FF reproduction is continued until the end point of section S1 is reached or exceeded.

When the end point of section S1 is reached or exceeded, controller 2120 controls drive control circuit 2106

to access the start position of the next section, that is to a position indicated by arrow 26<sub>3</sub> of Fig. 26A, for resuming FF reproduction at the leading end of section S2. FF reproduction continues in accordance with the above-described operation to the end point of section S3.

As will be clear to one of ordinary skill, the above-described operation may be adapted to achieve a FF reproduction of a program having any number of sections.

An example of a fast reverse (FR) reproduction operation according to the invention is described in the following. If fast reverse reproduction is commanded during reproduction of section S3 and the path\_descriptor information recorded in section S3 has not yet been stored in the entry point storing unit 2122, controller 2120 detects the path\_descriptor information associated with the path to be reproduced from the PSM of an arbitrary entry point in section S3, and that path\_descriptor information is stored in storing unit 2122.

Controller 2120 controls device 2100 to sequentially access the recorded entry points in accordance with the location information regarding forward and backward adjacent entry points stored in the PSD and to reproduce the I-picture placed directly after the access entry point. The sector address of the entry point being accessed is compared to the sector address indicated by arrow 26<sub>2</sub> of Fig. 26C stored in

the entry point storing unit 2122, and FR reproduction is continued until the start point of section S3 is reached or exceeded.

When the start point of section S3 is reached or exceeded, controller 2120 controls drive control circuit 2106 to access the last entry point of the previous section, that is to a position indicated by arrow 26<sub>4</sub> of Fig. 26C, for resuming FR reproduction at the last entry point of section S2.

Controller 2120 detects the path\_descriptor information associated with the path to be reproduced from the PSM of an entry point in section S2, and that path\_descriptor information is stored in storing unit 2122. Controller 2120 then controls device 2100 to sequentially access the recorded entry points and compares the sector address of the entry point being accessed with the sector address stored in the entry point storing unit 2122, indicated by arrow 26<sub>2</sub> of Fig. 26B. FR reproduction is continued until the start point of section S2 is reached or exceeded.

When the start point of section S2 is reached or exceeded, controller 2120 controls drive control circuit 2106 to access the last entry point of the previous section, that is to a position indicated by arrow 26<sub>4</sub> of Fig. 26B, for resuming FR reproduction at the last entry point of section S1. Controller 2120 detects the path\_descriptor information



associated with the path to be reproduced from the PSM of an entry point in section S1, and that path\_descriptor information is stored in storing unit 2122.

In section S1, pX\_offset\_previous\_section will contain a zero value indicating that a prior section is not present. Accordingly, controller 2120 allows reproduction of section S1 to proceed to the start of the section, as shown by arrow 26, in Fig. 26A, before reproduction is terminated.

As will be clear to one of ordinary skill, the above-described operation may be adapted to achieve a FR reproduction of a program having any number of sections.

An example of a track searching reproduction operation according to the invention is described in the following. If forward track search or backwards track search reproduction is commanded and the path\_descriptor information has not yet been stored in the entry point storing unit 2122, controller 2120 detects the PSM of the entry point near to the current point while detecting from plural path\_descriptors present in each path in the PSM the path\_descriptor information associated with the path to be reproduced, and that path\_descriptor information is stored in storing unit 2122.

Controller 2120 controls drive control circuit 2106 to access the position in the path descriptor information represented by the pX\_offset\_next\_track information,

associated with arrow 27<sub>a</sub> of Fig. 27. Since the information from which the leading position of the track directly preceding and directly succeeding the track is recorded as pX\_offset\_previous track information and pX\_offset\_next\_track information in the path\_descriptor information of the entry point at the leading end of the track, the leading end of the track preceding or succeeding the track by a number of tracks can be accessed by repeating the accessing operation.

Figs. 27A, 27B and 27C illustrate examples of entry points arranged in each section. The positions represented by pX\_offset\_previous\_track information are indicated by arrows 27<sub>a</sub> and the positions represented by pX\_offset\_next\_track information are indicated by arrow 27<sub>b</sub>.

Both pX\_offset\_previous\_track information and pX\_offset\_next\_track information are recorded at an entry point. As shown in Figs. 27A, 27B and 27C, since pX\_offset\_previous\_track information and pX\_offset\_next\_track information specify the positions of the starting points of the directly preceding and directly succeeding tracks beyond the boundaries of the current section, the starting points of tracks can be speedily and correctly accessed even when the path comprises plural sections.

Analogously, a time code search may also be achieved utilizing path descriptor information. In response to a command to search for a particular time code, controller 2120

may access entry points in other sections to locate the entry point having a particular time code according to the processes described above in connection with FF reproduction and FR reproduction. Alternatively, search for an entry point having a particular time code may be achieved by initially sequentially detecting the time code of the entry point of the leading end and/or the end point of each section. From the relative magnitudes of the time codes and by having access to the entry points in other sections as described above, controller 2120 may determine in which section lies the targeted time code.

The above-described operations may utilize time code information and/or track number information recorded in path\_descriptor information or time code\_descriptor information of each entry point.

In another embodiment of the reproducing device of Fig. 21, a less expensive reproducing device may be constructed by limiting the functionality of controller 2120. Specifically, such a device may not be capable of detecting path\_descriptor information sufficiently during reproduction or special reproduction operations. In such a reproducing device, reproduction and fast reproduction in the forward and reverse directions may be achieved for a particular path which is constituted by only one section by reading out and storing the leading points and end points of the path from

table-of-contents (TOC) information prior to reproduction of the program. If time code information or track number information need not be displayed, path\_descriptor information need not be reproduced during a reproduction operation. A controller 2120 which cannot reproduce path\_descriptor information can be constructed at a lower cost and hence an inexpensive reproducing device may be produced.

In the above-described embodiments, the information representing the data reproducing sequence (path) is placed and recorded in the path\_descriptor information in the program stream map (PSM) information included in the multiplexed data. This format enables a reproducing device not having abundant memory to access and store information required during a particular period of reproduction in order to control the reproducing sequence and to perform editing reproduction processing.

Alternatively, information representing the data reproducing sequence (path) may be collectively recorded outside the multiplexed data instead of being incorporated into the multiplexed data. Path\_descriptor information for each entry point may be combined with the sector addresses of the entry points and recorded at a single recording position, such as a table-of-contents area.

As a further alternative, the starting addresses and last entry point addresses of program sections may be arranged according to each path and recorded at a single recording position, such as a table-of-contents area. A reproducing device have a relatively large storage capacity may then access the address information prior to reproduction of the multiplexed data and thus have information sufficient for random access to any section of any path. As another alternative, the reproduction sequence of a particular path may be re-arranged and transferred to another information carrier with reference to only table of contents data and without reproducing the multiplexed data itself.

Although illustrative embodiments of the present invention and modifications thereof have been described in detail herein, it is to be understood that this invention is not limited to these precise embodiments and modifications, and that other modifications and variations may be affected therein by one skilled in the art without departing from the scope and spirit of the invention as defined by the appended claims.

## CLAIMS

1. Information carrier on which an information signal is recorded, the signal representing picture information intended to be displayed on a picture screen, the picture information comprising video information of at least a single video program and control information for displaying various versions of the video program, characterized in that the control information comprises path information indicative of one or more versions of video information sections to be reproduced in a linked fashion, the path information being indicative of sections to be reproduced consecutively.

2. Information carrier as claimed in Claim 1, characterized in that the video information of a video program is subdivided into two portions, the first portion comprising the video information of a basic version and the second portion comprising additional video information, and a version comprising at least one section of the additional video information.

3. Information carrier as claimed in Claim 1 or 2, characterized in that the sections are addressable and in that the path information comprises addresses of sections to be displayed consecutively.

4. Information carrier as claimed in one of the Claims 1 to 3, characterized in that the path information comprises playtime information.

5. Information carrier as claimed in one of the Claims 1 to 4, characterized in that the path information comprises track information indicative of a subdivision into tracks, while the tracks are numbered independently for each video program.

6. Information carrier as claimed in one of the Claims 1 to 5, characterized in that path information for displaying each version is recorded in an information carrier area that can be located.

7. Information carrier as claimed in one of the Claims 1 to 6, characterized in that path information is recorded on the information carrier near to entry points, while playback is possible from the entry points without the use of previous picture information.

8. Information carrier as claimed in Claim 7, characterized in that the information carrier is subdivided into addressable sectors and in that the path information near to an entry point comprises address information relative to the respective entry point.

9. Information carrier as claimed in Claim 7 or 8, characterized in that the video program is subdivided into tracks and in that the path information near to an entry

point comprises address information indicative of the beginning of the next track in the respective version.

10. Information carrier as claimed in one of the Claims 7 to 9, characterized in that the path information near to an entry point comprises address information of video information to be displayed beforehand.

11. Information carrier as claimed in one of the Claims 7 to 10, characterized in that the path information near to an entry point comprises time code information indicative of the playtime from the beginning of the respective version.

12. Device for reading an information carrier on which an information signal is recorded, the signal representing picture information intended to be displayed on a picture screen, the picture information comprising video information of at least a single video program and control information for displaying various versions of the video program, the device comprising first means (80, 81) for recovering the picture information and control means (84) for selectively reproducing the video program in response to the control information, characterized in that the control information comprises path information indicative of one or more versions of video information sections to be reproduced in linked fashion, the path information being indicative of sections to be reproduced consecutively, and in that the device



comprises second means (85) for recovering the path information and in that the control means (84) are adapted for consecutively reproducing the video program sections in response to the path information.

13. Device as claimed in Claim 12, characterized in that the path information comprises for each path the playtime information of the respective version and in that the device comprises means for displaying the playtime in response to the path information.

14. Device as claimed in Claim 12 or 13, characterized in that the path information for displaying each version is recorded in a locatable area of the information carrier and in that the second means are adapted for locating the area.

15. Device as claimed in one of the Claims 12 to 14, characterized in that path information is recorded on the information carrier near to entry points, while playback is possible from the entry points without the use of previous picture information, and in that the second means are adapted for recovering the path information near to entry points.

16. Device as claimed in Claim 15, characterized in that the path information near to an entry point comprises address information of video information to be displayed beforehand, and in that the control means are adapted for displaying the picture information in reverse direction in response to said addresses.

17. Device as claimed in Claim 15 or 16, characterized in that the path information near to an entry point comprises time code information indicative of the playtime from the beginning of the respective version, and in that the first means are adapted for displaying the picture information in response to the time code information.

18. Device for providing an information carrier on which an information signal is recorded, the signal representing picture information intended to be displayed on a picture screen, the picture information comprising video information of at least a single video program and control information for displaying various versions of the video program, the device comprising coding means (93) for coding the picture information and recording means (95, 96) for recording the information signal on the information carrier, characterized in that the control information comprises path information indicative of one or more versions of video information sections to be shown in linked fashion, the path information being indicative of sections to be displayed consecutively and in that the device comprises generator means (94) for generating the path information and means (94) for adding the path information to the picture information.

19. Method of transmitting picture information intended for being displayed on a picture screen via an information carrier on which an information signal

representing picture information is recorded, this picture information comprising video information of at least one video program and control information for displaying various versions of the video program, characterized in that the control information comprises path information indicative of one or more versions of video information sections to be shown in a linked fashion, the path information being indicative of sections to be displayed consecutively.

20. A method for displaying one of a plurality of versions of a program recorded on an information carrier, said method comprising the steps of:

displaying to a user a rating information regarding at least two versions from said plurality of versions;

receiving from said user a selection of one of said plurality of versions;

reproducing from said information carrier said one of said plurality of versions for display to the user.

21. The method according to claim 20 wherein said step of displaying rating information comprises the steps of:

displaying to the user a plurality of country identification information; and

receiving from the user a selection of a country corresponding to one of said plurality of country identification information.

22. The method according to claim 21 wherein said step of displaying rating information further comprises the steps of:

displaying to the user a plurality of ratings corresponding to said country; and

receiving from the user a selection of at least one of said plurality of ratings.

23. The method according to claim 21 further comprising the steps of:

displaying to the user a selected rating information regarding one of said plurality of versions if said selected rating information is consistent with said selection of at least one of said plurality of ratings.

24. The method according to claim 20 wherein said step of displaying rating information further comprises the steps of:

displaying to the user a plurality of ratings; and

receiving from the user a selection of at least one of said plurality of ratings.

25. The method according to claim 20 wherein said step of displaying rating information comprises the step of displaying to a user a rating information regarding each version from said plurality of versions.

26. The method according to claim 20 wherein said step of displaying rating information comprises the steps of:

accessing at least one preselected user rating preference; and

displaying to the user a preselected rating information regarding one of said plurality of versions if said preselected rating information is consistent with said prestored user rating preference.

27. An apparatus for displaying one of a plurality of versions of a program recorded on an information carrier, said apparatus comprising:

means for displaying to a user a rating information regarding at least two versions from said plurality of versions;

means for receiving from said user a selection of one of said plurality of versions;

means for reproducing from said information carrier said one of said plurality of versions for display to the user.

28. The apparatus according to claim 27 wherein said means for displaying rating information comprises:

means for displaying to the user a plurality of country identification information; and

means for receiving from the user a selection of a country corresponding to one of said plurality of country identification information.

29. The apparatus according to claim 28 wherein said means for displaying rating information further comprises:

means for displaying to the user a plurality of ratings corresponding to said country; and

means for receiving from the user a selection of at least one of said plurality of ratings.

30. The apparatus according to claim 28 further comprising:

means for displaying to the user a selected rating information regarding one of said plurality of versions if said selected rating information is consistent with said selection of at least one of said plurality of ratings.

31. The apparatus according to claim 27 wherein said means for displaying rating information further comprises:

means for displaying to the user a plurality of ratings; and

means for receiving from the user a selection of at least one of said plurality of ratings.

32. The apparatus according to claim 26 wherein said means for displaying rating information comprises means for displaying to a user a rating information regarding each version from said plurality of versions.

33. The apparatus according to claim 27 wherein said means for displaying rating information comprises:

means for accessing at least one preselected user rating preference; and

means for displaying to the user a preselected rating information regarding one of said plurality of versions if said preselected rating information is consistent with said prestored user rating preference.

34. A method for recording a plurality of versions of a program on an information carrier, said plurality of versions comprising a plurality of program sections, said method comprising the steps of:

encoding said plurality of program sections to produce a plurality of encoded program sections;

appending an address information to each of said plurality of encoded program sections;

appending a version information to each of said plurality of encoded program sections; and

recording said plurality of encoded program sections, including said address information and said version information, on said information carrier.

35. The method according to claim 34 wherein said step of encoding comprises the steps of:

intra-coding said plurality of program sections to produce I-frames; and

predictive coding said plurality of program sections to produce P-frames.

36. The method according to claim 34 wherein said step of appending an address information comprises the step of appending a start address information and an end address information to each of said plurality of encoded program sections.

37. The method according to claim 36 wherein said step of appending an address information further comprises the step of appending a next section start address information and a previous section last entry point information to each of said plurality of encoded program sections.

38. The method according to claim 37 wherein said step of appending an address information further comprises the step of appending an adjacent entry point address information to each of said plurality of encoded program sections.

39. The method according to claim 34 further comprising the step of appending a time code information to each of said plurality of encoded program sections.

40. The method according to claim 39 wherein said step of appending a time code information comprises the step of appending time code information regarding a timing of each of said plurality of encoded program sections relative to a leading end of at least one of said plurality of versions.

41. The method according to claim 34 further comprising the step of appending a track number information to each of said plurality of encoded program sections.



42. The method according to claim 41 wherein said step of appending a track number information comprises the step of appending track number information regarding a track indication of each of said plurality of encoded program sections relative to a leading end of at least one of said plurality of versions.

43. The method according to claim 34 wherein said step of appending a version information comprises the step of appending at least one path number to each of said plurality of encoded program sections.

44. The method according to claim 34 wherein said step of appending a version information comprises the step of appending at least one rating information to each of said plurality of encoded program sections.

45. The method according to claim 34 wherein said step of appending a version information comprises the step of appending at least one version identification information to each of said plurality of encoded program sections.

46. The method according to claim 34 wherein said step of appending a version information comprises the step of appending at least one path descriptor information to each of said plurality of encoded program sections.

47. The method according to claim 34 wherein said step of recording comprises the steps of:

recording a first completed access unit immediately prior to a jump point on said information carrier; and

recording a second completed access unit immediately following said jump point on said information carrier.

48. The method according to claim 34 wherein said step of recording comprises the steps of:

recording a first completed access unit immediately prior to each respective jump point on said information carrier; and

recording a second completed access unit immediately following said each respective jump point on said information carrier.

49. The method according to claim 34 wherein said step of recording comprises the steps of:

recording a first plurality of access units on a first side of a jump point; and

recording a second plurality of access units on a second side of said jump point without recording an access unit which requires for decoding one of a prediction and a reference with respect to one of said first plurality of access units.

50. The method according to claim 34 wherein one of said plurality of versions comprises a single program section on said information carrier.

51. Apparatus for recording a plurality of versions of a program on an information carrier, said plurality of versions comprising a plurality of program sections, said apparatus comprising:

means for encoding said plurality of program sections to produce a plurality of encoded program sections;

means for appending an address information to each of said plurality of encoded program sections;

means for appending a version information to each of said plurality of encoded program sections; and

means for recording said plurality of encoded program sections, including said address information and said version information, on said information carrier.

52. The apparatus according to claim 51 wherein said means for encoding comprises:

means for intra-coding said plurality of program sections to produce I-frames; and

means for predictive coding said plurality of program sections to produce P-frames.

53. The apparatus according to claim 51 wherein said means for appending an address information comprises means for appending a start address information and an end address information to each of said plurality of encoded program sections.

54. The apparatus according to claim 53 wherein said means for appending an address information further comprises means for appending a next section start address information and a previous section last entry point information to each of said plurality of encoded program sections.

55. The apparatus according to claim 54 wherein said means for appending an address information further comprises means for appending an adjacent entry point address information to each of said plurality of encoded program sections.

56. The apparatus according to claim 51 further comprising means for appending a time code information to each of said plurality of encoded program sections.

57. The apparatus according to claim 56 wherein said means for appending a time code information comprises means for appending time code information regarding a timing of each of said plurality of encoded program sections relative to a leading end of at least one of said plurality of versions.

58. The apparatus according to claim 51 further comprising means for appending a track number information to each of said plurality of encoded program sections.

59. The apparatus according to claim 58 wherein said means for appending a track number information comprises means for appending track number information regarding a

track indication of each of said plurality of encoded program sections relative to a leading end of at least one of said plurality of versions.

60. The apparatus according to claim 51 wherein said means for appending a version information comprises means for appending at least one path number to each of said plurality of encoded program sections.

61. The apparatus according to claim 51 wherein said means for appending a version information comprises means for appending at least one rating information to each of said plurality of encoded program sections.

62. The apparatus according to claim 51 wherein said means for appending a version information comprises means for appending at least one version identification information to each of said plurality of encoded program sections.

63. The apparatus according to claim 51 wherein said means for appending a version information comprises means for appending at least one path descriptor information to each of said plurality of encoded program sections.

64. The apparatus according to claim 51 wherein said means for recording comprises:

means for recording a first completed access unit immediately prior to a jump point on said information carrier; and

means for recording a second completed access unit immediately following said jump point on said information carrier.

65. The apparatus according to claim 51 wherein said means for recording comprises:

means for recording a first completed access unit immediately prior to each respective jump point on said information carrier; and

means for recording a second completed access unit immediately following said each respective jump point on said information carrier.

66. The apparatus according to claim 51 wherein said means for recording comprises:

means for recording a first plurality of access units on a first side of a jump point; and

means for recording a second plurality of access units on a second side of said jump point without recording an access unit which requires for decoding one of a prediction and a reference with respect to one of said first plurality of access units.

67. The apparatus according to claim 51 wherein one of said plurality of versions comprises a single program section on said information carrier.

68. A method for reproducing one of a plurality of versions of a program recorded on an information carrier,

said plurality of versions comprising a plurality of program sections, said method comprising the steps of:

reproducing from said information carrier a first program section that includes a plurality of version information and a plurality of address information;

detecting in said first program section a version information corresponding to said one of said plurality of versions and an address information corresponding to said version information; and

reproducing from said information carrier a second program section according to said address information.

69. The method according to claim 68 further comprising the steps of:

detecting in said second program section a second version information corresponding to said one of said plurality of versions and a second address information corresponding to said second version information; and

reproducing from said information carrier a third program section according to said second address information.

70. The method according to claim 68 further comprising the step of receiving from a user a selection indicating said one of said plurality of versions.

71. The method according to claim 68 wherein said version information comprises a version identification information.

72. The method according to claim 68 wherein said version information comprises a rating information.

73. The method according to claim 68 wherein said version information comprises an entry packet information.

74. The method according to claim 68 wherein said version information comprises a path descriptor information.

75. The method according to claim 68 further comprising the step of displaying to a user said first program section and said second program section without a perceptible interruption in display.

76. The method according to claim 68 wherein said step of detecting comprises the step of detecting an entry point.

77. The method according to claim 76 wherein said entry point is an entry sector.

78. The method according to claim 76 wherein said entry point is an entry packet.

79. The method according to claim 76 wherein said entry point is a path descriptor area.

80. The method according to claim 76 wherein said address information comprises a next section start address information.

81. The method according to claim 68 wherein each of said plurality of program sections includes a time code information and wherein said step of reproducing a first program section comprises the step of reproducing a first



time code information and wherein said step of reproducing a second program section comprises the step of reproducing a second time code information.

82. The method according to claim 68 wherein each of said plurality of program sections includes a track number information and wherein said step of reproducing a first program section comprises the step of reproducing a first track number information and wherein said step of reproducing a second program section comprises the step of reproducing a second track number information.

83. An apparatus for reproducing one of a plurality of versions of a program recorded on an information carrier, said plurality of versions comprising a plurality of program sections, said apparatus comprising:

means for reproducing from said information carrier a first program section that includes a plurality of version information and a plurality of address information;

means for detecting in said first program section a version information corresponding to said one of said plurality of versions and an address information corresponding to said version information; and

means for reproducing from said information carrier a second program section according to said address information.

84. The apparatus according to claim 83 further comprising:

means for detecting in said second program section a second version information corresponding to said one of said plurality of versions and a second address information corresponding to said second version information; and

means for reproducing from said information carrier a third program section according to said second address information.

85. The apparatus according to claim 83 further comprising means for receiving from a user a selection indicating said one of said plurality of versions.

86. The apparatus according to claim 83 wherein said version information comprises a rating information.

87. The apparatus according to claim 83 further comprising means for displaying to a user said first program section and said second program section without a perceptible interruption in display.

88. The apparatus according to claim 83 wherein said means for detecting comprises means for detecting an entry point.

89. The apparatus according to claim 83 wherein each of said plurality of program sections includes a time code information and wherein said means for reproducing a first program section comprises means for reproducing a first time code information and wherein said means for reproducing a

101

second program section comprises means for reproducing a second time code information.

90. The apparatus according to claim 83 wherein each of said plurality of program sections includes a track number information and wherein said means for reproducing a first program section comprises means for reproducing a first track number information and wherein said means for reproducing a second program section comprises means for reproducing a second track number information.

91. A method for reproducing one of a plurality of versions of a program recorded on an information carrier, said plurality of versions comprising a plurality of program sections, said method comprising the steps of:

reproducing from said information carrier a version information corresponding to said one of a plurality of versions and an address information corresponding to said version information; and

reproducing from said information carrier a program section according to said address information.

92. The method according to claim 91 wherein said step of reproducing comprises the step of reproducing a table of contents information.

93. The method according to claim 92 further comprising the step of reproducing from said information

102

carrier a plurality of program sections according to said  
address information.

1/30




FIG. 1




FIG. 2




FIG. 3

2/30




FIG. 4




FIG. 5

3/30




FIG.6




FIG.7

4/30

Syntax	No. of bits	Mnemonic
path_descriptor() {		
descriptor_tag	8	uimbsbf
descriptor_length	8	uimbsbf
reserved	5	bslbf
path_number	3	uimbsbf
reserved	4	bslbf
PTS[32..30]	3	bslbf
marker	1	bslbf
PTS[29..15]	15	bslbf
marker	1	bslbf
PTS[14..0]	15	bslbf
marker	1	bslbf
track_number	16	uimbsbf
pX_sectors_to_read	24	uimbsbf
pX_sectors_from_start	24	uimbsbf
pX_offset_next_section	32	imsbf
pX_offset_previous_section	32	imsbf
pX_offset_next_track	32	imsbf
pX_offset_start_track	32	imsbf
pX_track_tc_hours_1	4	bslbf
pX_track_tc_hours_2	4	bslbf
pX_track_tc_minutes_1	4	bslbf
pX_track_tc_minutes_2	4	bslbf
pX_track_tc_seconds_1	4	bslbf
pX_track_tc_seconds_2	4	bslbf
pX_track_tc_CC	2	bslbf
pX_track_tc_frames_1	2	bslbf
pX_track_tc_frames_2	4	bslbf
pX_path_tc_hours_1	4	bslbf
pX_path_tc_hours_2	4	bslbf
pX_path_tc_minutes_1	4	bslbf
pX_path_tc_minutes_2	4	bslbf
pX_path_tc_seconds_1	4	bslbf
pX_path_tc_seconds_2	4	bslbf
pX_path_tc_CC	2	bslbf
pX_path_tc_frames_1	2	bslbf
pX_path_tc_frames_2	4	bslbf
}		

FIG.6A






FIG.6B




FIG.6C

6/30




FIG. 8





FIG. 9

7/30

**FIG.10**

8/30

BP	Field name	Content
1	Volume Descriptor Type	numerical value
2 to 6	Standard Identifier	CD001
7	Volume Descriptor Version	numerical value
8	Unused Field	(00) byte
9 to 40	System Identifier	a-characters
41 to 72	Volume Identifier	d-characters
73 to 80	Unused Field	(00) bytes
81 to 88	Volume Space Size	numerical value
89 to 120	Unused Field	(00) bytes
121 to 124	Volume Set Size	numerical value
125 to 128	Volume Sequence Number	numerical value
129 to 132	Logical Block Size	numerical value
133 to 140	Path Table Size	numerical value
141 to 144	Location of Occurrence of Type L Path Table	numerical value
145 to 148	Location of Optional Occurrence of Type L Path Table	numerical value
149 to 152	Location of Occurrence of Type M Path Table	numerical value
153 to 156	Location of Optional Occurrence of Type M Path Table	numerical value
157 to 190	Directory Record for Root Directory	34 bytes
191 to 318	Volume Set Identifier	d-characters
319 to 446	Publisher Identifier	a-characters
447 to 574	Data Preparer Identifier	a-characters
575 to 702	Application Identifier	a-characters
703 to 739	Copyright File Identifier	d-characters, SEPARATOR 1, SEPARATOR 2
740 to 776	Abstract File Identifier	d-characters, SEPARATOR 1, SEPARATOR 2
777 to 813	Bibliographic File Identifier	d-characters, SEPARATOR 1, SEPARATOR 2
814 to 830	Volume Creation Date and Time	Digit(s), numerical value
831 to 847	Volume Modification Date and Time	Digit(s), numerical value
848 to 864	Volume Expiration Date and Time	Digit(s), numerical value
865 to 881	Volume Effective Date and Time	Digit(s), numerical value
882	File Structure Version	numerical value
883	(Reserved for future standardization)	(00) byte
884 to 1 395	Application Use	not specified
1 396 to 2 048	(Reserved for future standardization)	(00) bytes

FIG.11

9/30

Syntax	No. of bits	Mnemonic
<b>disc_toc ()</b>		
dvd_signature	64	bslbf
dvd_version	32	bslbf
length	16	uimsbf
toc_type	8	bslbf
reserved	8	bslbf
album()		
catalogue()		
reserved	16	uimsbf
number_of_programs (NOP)	16	bslbf
rating_definitions_offset	32	uimsbf
program_linkage_offset	32	uimsbf
disc_track_offset	32	uimsbf
program_toc_pointers_offset	32	uimsbf
disc_play_time_offset	32	uimsbf
disc_name_offset	32	uimsbf
disc_date_offset	32	uimsbf
disc_copyright_offset	32	uimsbf
disc_publisher_offset	32	uimsbf
reserved	288	bslbf
rating_definitions()		
program_linkage()		
disc_tracks()		
program_toc_pointers()		
disc_play_time()		
disc_name()		
disc_date()		
disc_copyright()		
disc_publisher()		

FIG.12

10/30

Syntax	No. of Bits	Mnemonic
disc_tracks() {		
for(i=0; i < 8; i++){		
number_of_tracks(NOT)	16	uimsbf
reserved	16	bslbf
for (t=0; t < NOT; t++) {		
program_number	16	uimsbf
track_number	16	uimsbf
start_lsa	32	uimsbf
last_lsa	32	uimsbf
last_es_lsa	32	uimsbf
stoppiing_stc	32	uimsbf
playing_time()		
}		
}		
}		

FIG.12A

11/30

Syntax	No. of Bits	Mnemonic
<b>program_toc(){</b>		
dvd_signature	64	bslbf
dvd_version	32	bslbf
length	16	uimsbf
toc_type	8	bslbf
reserved	8	bslbf
number_of_tracks (NOT)	16	uimsbf
reserved	16	bslbf
program_start_lsa	32	uimsbf
path_rating_assignment_offset	32	uimsbf
for (i=0; i<8; i++){		
program_tracks_offset_i	32	uimsbf
}		
elementary_stream_info_offset	32	uimsbf
program_play_times_offset	32	uimsbf
program_name_offset	32	uimsbf
track_names_offset	32	uimsbf
program_date_offset	32	uimsbf
track_dates_offset	32	uimsbf
program_copyright_offset	32	uimsbf
program_publisher_offset	32	uimsbf
reserved	288	bslbf
path_rating_assignments()		
for (i=0; i<8; i++){		
if (program_chapters_offset_i>0){		
program_tracks()		
entry_points()		
path_table()		
}		
}		
elementary_stream_info()		
program_play_times()		
program_name()		
track_names()		
program_date()		
track_dates()		
program_copyright()		
program_publisher()		
}		

FIG.13

12/30

Syntax	No. of Bits	Mnemonic
<b>program_tracks() {</b>		
<b>number_of_path_tracks(NOPT)</b>	<b>16</b>	<b>uimsbf</b>
<b>reserved</b>	<b>16</b>	<b>bslbf</b>
<b>for (t=0; t &lt; NOPT; t++) {</b>		
<b>reserved</b>	<b>16</b>	<b>bslbf</b>
<b>track_number</b>	<b>16</b>	<b>uimsbf</b>
<b>start_rsa</b>	<b>32</b>	<b>uimsbf</b>
<b>last_rsa</b>	<b>32</b>	<b>uimsbf</b>
<b>last_es_rsa</b>	<b>32</b>	<b>uimsbf</b>
<b>stoppiing_stc</b>	<b>32</b>	<b>uimsbf</b>
<b>track_playing_time()</b>	<b>32</b>	<b>uimsbf</b>
<b>}</b>		
<b>}</b>		

FIG.13A

Syntax	No. of Bits	Mnemonic
<b>path_table() {</b>		
<b>number_of_sections(NOCH)</b>	<b>32</b>	<b>uimsbf</b>
<b>for (ch=0; ch &lt; NOCH; ch++) {</b>		
<b>start_rsa</b>	<b>32</b>	<b>uimsbf</b>
<b>last_rsa</b>	<b>32</b>	<b>uimsbf</b>
<b>stoppiing_stc</b>	<b>32</b>	<b>uimsbf</b>
<b>last_es_rsa</b>	<b>32</b>	<b>uimsbf</b>
<b>}</b>		
<b>}</b>		

FIG.13B



13/30




FIG.14




FIG.15A

15/30




FIG.15B

16/30

Syntax	No. of Bits	Mnemonic
PES_packet(){		
packet_start_code_prefix	24	bslbf
stream_id	8	uimsbf
PES_packet_length	16	uimsbf
if (stream_id != program_stream_map		
&& stream_id !=padding_stream		
&& stream_id !=private_stream_2		
&& stream_id !=ECM		
&& stream_id !=EMM		
&& stream_id !=program_stream_directory		
&& stream_id !=DSMCC_stream		
&& stream_id !=ITU-T Rec. H.222.1 type E_stream){		
'10'	2	bslbf
PES_scrambling_control	2	bslbf
PES_priority	1	bslbf
data_alignment_indicator	1	bslbf
copyright	1	bslbf
original_or_copy	1	bslbf
PTS_DTS_flags	2	bslbf
ESCR_flag	1	bslbf
ES_rate_flag	1	bslbf
DSM_trick_mode_flag	1	bslbf
additional_copy_info_flag	1	bslbf
PES_CRC_flag	1	bslbf
PES_extension_flag	1	bslbf
PES_header_data_length	8	uimsbf
if (PTS_DTS_flag == '10') {		
'0010'	4	bslbf
PTS [32..30]	3	bslbf
marker_bit	1	bslbf
PTS [29..15]	15	bslbf
marker_bit	1	bslbf
PTS [14..0]	15	bslbf
marker_bit	1	bslbf
}		
if (PTS_DTS_flags == '11') {		
'0011'	4	bslbf
PTS [32..30]	3	bslbf
marker_bit	1	bslbf
PTS [29..15]	15	bslbf
marker_bit	1	bslbf
PTS [14..0]	15	bslbf
marker_bit	1	bslbf
'0001'	4	bslbf
DTS [32..30]	3	bslbf
marker_bit	1	bslbf
DTS [29..15]	15	bslbf

FIG.16A

17/30

Syntax	No. of Bits	Mnemonic
marker_bit	1	bslbf
DTS [14..0]	15	bslbf
marker_bit	1	bslbf
}		
if (ESCR_flag == '1') {		
reserved	2	bslbf
ESCR_base [32..30]	3	bslbf
marker_bit	1	bslbf
ESCR_base [29..15]	15	bslbf
marker_bit	1	bslbf
ESCR_base [14..0]	15	bslbf
marker_bit	1	bslbf
ESCR_extension	9	uimsbf
marker_bit	1	bslbf
}		
if (ES_rate_flag == '1') {		
marker_bit	1	bslbf
ES_rate	22	uimsbf
marker_bit	1	bslbf
}		
if (DSM_trick_mode_flag == '1') {		
trick_mode_control	3	uimsbf
if (trick_mode_control == fast_forward) {		
field_id	2	bslbf
intra_slice_refresh	1	bslbf
frequency_truncation	2	bslbf
}		
else if (trick_mode_control == slow_motion) {		
rep_cntrl	5	uimsbf
}		
else if (trick_mode_control == freeze_frame) {		
field_id	2	uimsbf
reserved	3	bslbf
}		
else if (trick_mode_control == fast_reverse) {		
field_id	2	bslbf
intra_slice_refresh	1	bslbf
frequency_truncation	2	bslbf
else if (trick_mode_control == slow_reverse) {		
rep_cntrl	5	uimsbf
}		
else		
reserved	5	bslbf
}		
if (additional_copy_info_flag == '1') {		
marker_bit	1	bslbf
additional_copy_info	7	bslbf

FIG.16B

18/30

Syntax	No. of Bits	Mnemonic
<pre>         }         if (PES_CRC_flag == '1') {             previous_PES_packet_CRC         }         if (PES_extension_flag == '1') {             PES_private_data_flag             pack_header_field_flag             program_packet_sequence_counter_flag             P-STD_buffer_flag             reserved             PES_extension_flag_2             if (PES_private_data_flag == '1') {                 PES_private_data             }             if (pack_header_field_flag == '1') {                 pack_field_length                 pack_header()             }             if (program_packet_sequence_counter_flag == '1') {                 marker_bit                 program_packet_sequence_counter                 marker_bit                 MPEG1_MPEG2_identifier                 original_stuff_length             }             if (P-STD_buffer_flag == '1') {                 '01'                 P-STD_buffer_scale                 P-STD_buffer_size             }             if (PES_extension_flag_2 == '1') {                 marker_bit                 PES_extension_field_length                 for (i=0; i&lt;PES_extension_field_length; i++)             {                 reserved             }         }         for (i=0; i&lt;N1; i++) {             stuffing_byte         }         for (i=0; i&lt;N2; i++) {             PES_packet_data_byte </pre>	<pre> 16 1 1 1 1 3 1 128 8 1 7 1 1 6 2 1 13 1 7 8 8 8 </pre>	<pre> bslbf bslbf bslbf bslbf bslbf bslbf bslbf bslbf uimbsf bslbf uimbsf bslbf bslbf uimbsf bslbf bslbf uimbsf bslbf uimbsf bslbf bslbf </pre>

FIG.16C

19/30

Syntax	No. of Bits	Mnemonic
<pre>         }     }     else if (stream_id == program_stream_map        stream_id == private_stream_2        stream_id == ECM        stream_id == EMM        stream_id == program_stream_directory        stream_id == DSMCC_stream)        stream_id == ITU-T Rec. H.222.1 type E stream {         for (i=0; i&lt;PES_packet_length; i++) {             PES_packet_data_byte         }     }     else if (stream_id == padding_stream) {         for (i=0; i&lt;PES_packet_length; i++) {             padding_byte         }     } } </pre>	<p>8</p> <p>8</p>	<p>bslbf</p> <p>bslbf</p>

FIG.16D




FIG.17



21/30




FIG.18




FIG.19

23/30




FIG.20

24/30




FIG.21





FIG.22A

26/30

Syntax	No. of Bits	Mnemonic
<b>program_stream_map(){</b>		
<b>packet_start_code_prefix</b>	<b>24</b>	<b>bslbf</b>
<b>map_stream_id</b>	<b>8</b>	<b>uimsbf</b>
<b>program_stream_map_length</b>	<b>16</b>	<b>uimsbf</b>
<b>current_next_indicator</b>	<b>1</b>	<b>bslbf</b>
<b>reserved</b>	<b>2</b>	<b>bslbf</b>
<b>program_stream_map_version</b>	<b>5</b>	<b>uimsbf</b>
<b>reserved</b>	<b>7</b>	<b>bslbf</b>
<b>marker_bit</b>	<b>1</b>	<b>bslbf</b>
<b>program_stream_info_length</b>	<b>16</b>	<b>uimsbf</b>
<b>for (i=0;i&lt;N;i++){</b>		
<b>descriptor()</b>		
<b>}</b>		
<b>elementary_stream_map_length</b>	<b>16</b>	<b>uimsbf</b>
<b>for (i=0;i&lt;N1;i++){</b>		
<b>stream_type</b>	<b>8</b>	<b>uimsbf</b>
<b>elementary_stream_id</b>	<b>8</b>	<b>uimsbf</b>
<b>elementary_stream_info_length</b>	<b>16</b>	<b>uimsbf</b>
<b>for (i=0;i&lt;N2;i++){</b>		
<b>descriptor()</b>		
<b>}</b>		
<b>}</b>		
<b>CRC_32</b>	<b>32</b>	<b>rpchof</b>
<b>}</b>		


FIG.22B

27/30



EXAMPLE IN WHICH EACH ACCESS UNIT  
OF EACH ELEMENTARY STREAM IS  
COMPLETED AT JUMP POINT

FIG.23A




X...PADDING DATA  
AF...AUDIO FRAME (AUDIO ACCESS UNIT)  
I...I PICTURE (VIDEO ACCESS UNIT)  
B...B PICTURE (VIDEO ACCESS UNIT)

EXAMPLE IN WHICH EACH ACCESS UNIT  
OF EACH ELEMENTARY STREAM IS  
NOT COMPLETED AT JUMP POINT


FIG.23B

28/30



EXAMPLE IN WHICH PREDICTION  
(REFERENCE) IS NOT MADE ON  
BOTH SIDES OF JUMP POINT

FIG.24A



X...PADDING DATA  
AF...AUDIO FRAME (AUDIO ACCESS UNIT)  
I...I PICTURE (VIDEO ACCESS UNIT)  
P...P PICTURE (VIDEO ACCESS UNIT)  
B...B PICTURE (VIDEO ACCESS UNIT)

EXAMPLE IN WHICH PREDICTION  
(REFERENCE) IS MADE ON  
BOTH SIDES OF JUMP POINT

FIG.24B



29/30










FIG.25



30/30



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/JP 96/02188

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G11B20/00 H04N5/913 H04N7/16 G11B27/10 G11B27/28  
G11B27/34 G11B19/02 G11B20/12 H04N5/926 H04N9/804  
H04N5/937 H04N9/877 H04N5/85 //G11B7/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G11B H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO,A,95 12275 (TIME WARNER ENTERTAINMENT CO., L.P.) 4 May 1995  see abstract see page 1, line 4 - page 5, line 26 see page 8, line 13 - page 14, line 18 see page 18, line 4 - page 29, line 25 see page 30, line 23 - page 33, line 17 see page 36, line 27 - page 45, line 7 see page 47, line 9 - page 58, line 22	1-4,6,7, 11,12, 19-21, 23,27, 68-70, 72-74, 81, 83-86, 89,91-93
Y	---	75,87
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*&\* document member of the same patent family

Date of the actual completion of the international search

15 November 1996

Date of mailing of the international search report

1 1. 12. 96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+ 31-70) 340-3016

Authorized officer

Daalman, F

## INTERNATIONAL SEARCH REPORT

Inter nal Application No  
PCT/JP 96/02188

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO,A,94 03851 (DIGITAL PICTURES, INC.) 17 February 1994 see the whole document	75,87
A		1,12,19, 20,27, 68,83
P,X	--- EP,A,0 677 842 (K.K.TOSHIBA) 18 October 1995  see column 2, line 1 - line 52 see column 4, line 6 - column 5, line 49 see column 6, line 47 - column 20, line 37; claims 1-38 X: &WO,A,9512197 (publ. 04.05.1995)	1,2,6,7, 12,14, 18-20, 27, 34-36, 44,51, 52,61, 67-72, 83-86, 91-93
P,X	--- EP,A,0 675 493 (K.K.TOSHIBA) 4 October 1995	1-3,5-9, 12,14, 15, 18-20, 34-38, 41-43, 45,46, 50-55, 58-63, 67-74, 76-80, 82-86, 88,90-93
P,X	see the whole document	
P,X	--- EP,A,0 695 098 (SHARP K.K.) 31 January 1996  see column 3, line 26 - column 4, line 20 see column 7, line 43 - column 10, line 17 see column 11, line 40 - column 23, line 8 --- -/--	1,3,4,6, 12,14, 18,19

# INTERNATIONAL SEARCH REPORT

Inter    nal Application No  
PCT/JP 96/02188

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	EP,A,0 737 974 (K.K. TOSHIBA) 16 October 1996	1-4, 6-15, 17-22, 26,27, 32-36, 39,40, 43-46, 50-53, 56,57, 60-63, 67-74,81
E	see the whole document	83-86, 89,91-93
A	--- US,A,4 930 158 (VOGEL) 29 May 1990 cited in the application	1,12, 18-20, 27,34, 51,68, 83,91
	see the whole document	
A	--- US,A,5 172 111 (OLIVO, JR.) 15 December 1992	1,12, 18-20, 27,34, 51,68, 83,91
	see the whole document	
A	--- EP,A,0 644 692 (K.K.TOSHIBA) 22 March 1995	1,5-7,9, 12,14, 18-20, 27, 34-36, 41, 51-54, 58,68, 82,83, 91-93
	see the whole document	
A	--- EP,A,0 460 764 (N.N.PHILIPS'GLOEILAMPENFABRIEKEN) 11 December 1991 see the whole document	1,12,19
A	--- EP,A,0 651 392 (K.K.TOSHIBA ET AL.) 3 May 1995	1,6,11, 12,17, 20,27, 68, 81-83, 89-93
	see the whole document	
	--- -/--	

# INTERNATIONAL SEARCH REPORT

Inter national Application No  
PCT/JP 96/02188

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,A	EP,A,0 668 695 (VICTOR COMPANY OF JAPAN, LIMITED) 23 August 1995  see the whole document ---	1,12, 18-20, 27,34, 35,51, 52,68, 83,91
P,A	EP,A,0 689 206 (SONY CORPORATION) 27 December 1995  see the whole document A: &WO,A,95/16262 (publ. 15-06-1995) ---	1,12, 18-20, 27,34, 51,68, 83,91
A	EP,A,0 570 922 (SONY CORPORATION) 24 November 1993 see the whole document -----	